



#### > POWER UNDER FINE-TUNED CONTROL

90Nm carefully distributed to deliver a natural pedalling feeling in any circumstance. Perfect match for Sport and urban need. Everything enclosed in a compact design at only 3,2Kg.

#### > CONNECTION PORTS

- · Power
- Battery
- AUX
- Speed sensor
- Display
- Light rear
- Light front

## > TECHNOLOGY

Innovative Vectorial Logic to manage electronics
with customizable settings
4 Sided Torque sensor for a precise input control during pedaling.
36V lights management.

## > MOUNTING POINTS



|                           | EDGE                             |  |
|---------------------------|----------------------------------|--|
| Rated Power               | 250W                             |  |
| Rated Voltage             | 36V                              |  |
| Max Torque                | 90Nm                             |  |
| Internal Gear Stages      | 3                                |  |
| Weight                    | 3,2Kg                            |  |
| Communication             | UART/CAN BUS                     |  |
| Fixing Holes Pattern      | BH                               |  |
| Q-Factor                  | 177mm                            |  |
| Chain-line                | 49mm                             |  |
| Crank interface           | ISIS                             |  |
| Chainring options         | Direct Mount or BCD 104 - 30/44T |  |
| Coaster brake option      | No                               |  |
| Chain-guide and bashguard | ISCG05                           |  |







CASE AND

CCESSORIES



| CABLES COVER                         |
|--------------------------------------|
| CHAINLINE SPACER                     |
| LOCK NUT                             |
| SPEED SENSOR, MAGNET, CABLE & HOLDER |
|                                      |





# HIGH VISION with OLI Pre-Set





LIGHT FRONT CABLE & LIGHT REAR CABLE MOTOR TO BATTERY CABLE DISPLAY CABLE DIAGNOSTIC CABLE