

# MOVE-N

E-MOBILITY WITH NO FRILLS



**250W**  
Rated Power

**85Nm**  
Max Torque

**3,9Kg**  
Weight

eCITY

eCARGO

eTREKKING

## > OPTIMAL PERFORMANCE

Compatible with the most diffused mounting point pattern. This standardization ensures manufacturers the possibility of installation on existing frames, significantly reducing design investments.

Such flexibility is particularly advantageous in an industry where the speed of adaptation to emerging technologies is crucial.

## > TECHNOLOGY

MOVE-N incorporates the advanced technology of OLI eBike Systems.

This integration guarantees optimal performance and an improved driving experience, placing MOVE-N at the forefront of the evolution of electric mobility on two wheels.

## > CONNECTION PORTS

- Power
- Battery
- Speed sensor
- Display
- Light rear
- Light front

## > MOUNTING POINTS



	MOVE-N
Rated Power	250W
Rated Voltage	36V
Max Torque	85Nm
Internal Gear Stages	2
Weight	3,9Kg
Communication	UART
Fixing Holes Pattern	BH
Q-Factor	178mm
Chain-line	52mm (142mm/148mm boost)
Crank interface	ISIS
Chainring options	BCD 104 - 30/44T
Coaster brake option	Yes
Chain-guide and bashguard	Yes

DISPLAY



RING VISION



SIDE VISION



HIGH VISION

BATTERY



520 Wh  
integrated battery



630 Wh  
integrated battery



630 Wh  
semi-integrated battery  
for eCargo

CASE AND COVER



ACCESSORIES

- SPIDER
- LOCK NUT & TOOL
- SPEED SENSOR, MAGNET, CABLE & HOLDER
- CHAIN GUIDE

- LIGHT FRONT CABLE & LIGHT REAR CABLE
- MOTOR TO BATTERY CABLE
- DISPLAY CABLE
- DIAGNOSTIC CABLE