

**superior.**



# MODEL NOMENCLATURE

## FRAME MATERIAL

9

Carbon

6

Aluminium

## COMPONENTS QUALITY

.9

Highest



.1

Lowest

## E-BIKE CATEGORY

e

Power e-bikes

i

Light e-bikes

## USAGE

Team

Team models

RC

Race

DC

Down Country

GF

Gran Fondo

GR

Gravel

RR

Road Racing

## EXAMPLE

**XF 9.9 Team**

Model  
line

Frame  
Material

Components  
Quality

Usage



superior.

# XF 9.9 Team

Gloss Carbon / Red Carbon

MTB FULL-SUSPENSION / XF TEAM



# XF 9.6 Team

Gloss Carbon / Red Carbon

MTB FULL-SUSPENSION / XF TEAM



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|       |  |
|-------|--|
| FRAME | SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready |
|-------|--|

|                 |   |
|-----------------|---|
| SUSPENSION FORK | DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel |
|-----------------|---|

|            |                                  |
|------------|----------------------------------|
| REAR SHOCK | DT Swiss R232 ONE, size 190x45mm |
|------------|----------------------------------|

|                |  |
|----------------|--|
| BOTTOM BRACKET | SHIMANO BB-71-41A, PressFit, shell 41x92mm |
|----------------|--|

|         |   |
|---------|---|
| HEADSET | ACROS AZX-1305S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings |
|---------|---|

|           |  |
|-----------|--|
| REAR AXLE | SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black |
|-----------|--|

### DRIVETRAIN

|                |  |
|----------------|--|
| SHIFTERS RIGHT | SHIMANO XTR SW-M9250-IR, Di2, 12-speed |
|----------------|--|

|                 |  |
|-----------------|--|
| REAR DERAILLEUR | SHIMANO XTR RD-M9250, Shadow Plus Design |
|-----------------|--|

|          |                           |
|----------|---------------------------|
| CRANKSET | SHIMANO XTR FC-M9200, 36T |
|----------|---------------------------|

|          |  |
|----------|--|
| CASSETTE | SHIMANO XTR CS-M9200, 12-speed, 10-51T |
|----------|--|

|       |                      |
|-------|----------------------|
| CHAIN | SHIMANO XTR CN-M9100 |
|-------|----------------------|

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO XTR M9200, hydraulic disc brake |
|-------------|---|

|             |                         |
|-------------|-------------------------|
| ROTOR FRONT | SHIMANO RT-CL900, 180mm |
|-------------|-------------------------|

|            |   |
|------------|---|
| BRAKE REAR | SHIMANO XTR M9200, hydraulic disc brake |
|------------|---|

|            |                         |
|------------|-------------------------|
| ROTOR REAR | SHIMANO RT-CL900, 160mm |
|------------|-------------------------|

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss XRC 1200 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready |
|----------------|---|

|               |   |
|---------------|---|
| WHEELSET REAR | DT Swiss XRC 1200 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready |
|---------------|---|

|            |  |
|------------|--|
| TYRE FRONT | Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed |
|------------|--|

|           |  |
|-----------|--|
| TYRE REAR | Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed |
|-----------|--|

### COCKPIT

|           |                                   |
|-----------|-----------------------------------|
| HANDLEBAR | ONE Carbon Integrated Cockpit ICR |
|-----------|-----------------------------------|

|            |                   |
|------------|-------------------|
| GRIPS LEFT | ONE Race, Lock-On |
|------------|-------------------|

|             |                   |
|-------------|-------------------|
| GRIPS RIGHT | ONE Race, Lock-On |
|-------------|-------------------|

### PARTS

|        |                         |
|--------|-------------------------|
| SADDLE | Fizi:k Ridon X1, Carbon |
|--------|-------------------------|

|                |                                  |
|----------------|----------------------------------|
| SEATPOST LEVER | SRAM AXS POD, Dropper Post Lever |
|----------------|----------------------------------|

|          |                                      |
|----------|--------------------------------------|
| SEATPOST | SRAM Reverb AXS dropper post, 30.9mm |
|----------|--------------------------------------|

|                |                            |
|----------------|----------------------------|
| SEATPOST CLAMP | ONE CC-080A, 34.9mm, Black |
|----------------|----------------------------|

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19" (L) | 21" (XL) |
|--------------------------------|-----------|-----------|---------|----------|
| BB DROP (MM)                   | 42        | 42        | 42      | 42       |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482     | 533      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 605       | 625     | 645      |
| STACK HEIGHT (MM)              | 583       | 593       | 602     | 611      |
| REACH (MM)                     | 439       | 460       | 478     | 496      |
| SEAT TUBE ANGLE                | 76,3°     | 76,3°     | 76,3°   | 76,3°    |
| HEAD TUBE ANGLE                | 66,5°     | 66,5°     | 66,5°   | 66,5°    |
| REAR CENTER (MM)               | 430       | 430       | 430     | 430      |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110     | 120      |
| WHEELBASE (MM)                 | 1153      | 1179      | 1200    | 1222     |
| HANDLEBAR (MM)                 | 760/60    | 760/60    | 760/80  | 760/80   |
| CRANKSET (MM)                  | 170       | 170       | 175     | 175      |
| SEATPOST (MM)                  | 125       | 125       | 150     | 150      |

## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|       |  |
|-------|--|
| FRAME | SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready |
|-------|--|

|                 |   |
|-----------------|---|
| SUSPENSION FORK | DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel |
|-----------------|---|

|            |                                  |
|------------|----------------------------------|
| REAR SHOCK | DT Swiss R232 ONE, size 190x45mm |
|------------|----------------------------------|

|                |  |
|----------------|--|
| BOTTOM BRACKET | SHIMANO BB-71-41A, PressFit, shell 41x92mm |
|----------------|--|

|         |   |
|---------|---|
| HEADSET | ACROS AZX-1305S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings |
|---------|---|

|           |  |
|-----------|--|
| REAR AXLE | SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black |
|-----------|--|

### DRIVETRAIN

|                |                                       |
|----------------|---------------------------------------|
| SHIFTERS RIGHT | SHIMANO XT SW-M8250-IR, Di2, 12-speed |
|----------------|---------------------------------------|

|                 |   |
|-----------------|---|
| REAR DERAILLEUR | SHIMANO XT RD-M8250, Shadow Plus Design |
|-----------------|---|

|          |                          |
|----------|--------------------------|
| CRANKSET | SHIMANO XT FC-M8200, 34T |
|----------|--------------------------|

|          |                                       |
|----------|---------------------------------------|
| CASSETTE | SHIMANO XT CS-M8200, 12-speed, 10-51T |
|----------|---------------------------------------|

|       |                     |
|-------|---------------------|
| CHAIN | SHIMANO XT CN-M8100 |
|-------|---------------------|

### BRAKING SYSTEM

|             |  |
|-------------|--|
| BRAKE FRONT | SHIMANO XT M8200, hydraulic disc brake |
|-------------|--|

|             |                         |
|-------------|-------------------------|
| ROTOR FRONT | SHIMANO RT-CL800, 180mm |
|-------------|-------------------------|

|            |  |
|------------|--|
| BRAKE REAR | SHIMANO XT M8200, hydraulic disc brake |
|------------|--|

|            |                         |
|------------|-------------------------|
| ROTOR REAR | SHIMANO RT-CL800, 160mm |
|------------|-------------------------|

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss XRC 1700 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready |
|----------------|---|

|               |   |
|---------------|---|
| WHEELSET REAR | DT Swiss XRC 1700 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready |
|---------------|---|

|            |  |
|------------|--|
| TYRE FRONT | Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed |
|------------|--|

|           |  |
|-----------|--|
| TYRE REAR | Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.35", ADDIX Speed |
|-----------|--|

### COCKPIT

|           |                                   |
|-----------|-----------------------------------|
| HANDLEBAR | ONE Carbon Integrated Cockpit ICR |
|-----------|-----------------------------------|

|            |                   |
|------------|-------------------|
| GRIPS LEFT | ONE Race, Lock-On |
|------------|-------------------|

|             |                   |
|-------------|-------------------|
| GRIPS RIGHT | ONE Race, Lock-On |
|-------------|-------------------|

### PARTS

|        |                        |
|--------|------------------------|
| SADDLE | Fizi:k Ridon X5, Alloy |
|--------|------------------------|

|                |                                     |
|----------------|-------------------------------------|
| SEATPOST LEVER | SHIMANO SL-MT500-L, Seat post lever |
|----------------|-------------------------------------|

|          |                                       |
|----------|---------------------------------------|
| SEATPOST | ONE Sport Dropper Post, Alloy, 30.9mm |
|----------|---------------------------------------|

|                |                            |
|----------------|----------------------------|
| SEATPOST CLAMP | ONE CC-080A, 34.9mm, Black |
|----------------|----------------------------|

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19" (L)   | 21" (XL)  |
|--------------------------------|-----------|-----------|-----------|-----------|
| BB DROP (MM)                   | 42        | 42        | 42        | 42        |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482       | 533       |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 605       | 625       | 645       |
| STACK HEIGHT (MM)              | 583       | 593       | 602       | 611       |
| REACH (MM)                     | 439       | 460       | 478       | 496       |
| SEAT TUBE ANGLE                | 76,3°     | 76,3°     | 76,3°     | 76,3°     |
| HEAD TUBE ANGLE                | 66,5°     | 66,5°     | 66,5°     | 66,5°     |
| REAR CENTER (MM)               | 430       | 430       | 430       | 430       |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110       | 120       |
| WHEELBASE (MM)                 | 1153      | 1179      | 1200      | 1222      |
| HANDLEBAR (MM)                 | 760/60    | 760/60    | 760/80    | 760/80    |
| CRANKSET (MM)                  | 170       | 170       | 175       | 175       |
| SEATPOST (MM)                  | L408/T125 | L408/T125 | L458/T150 | L458/T150 |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# XF 9.7 RC

Matte Carbon / Smoke Chrome

MTB FULL-SUSPENSION / XF RC



# XF 9.6 RC

Gloss Grey / Coral Red

MTB FULL-SUSPENSION / XF RC



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready |
| SUSPENSION FORK | DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel  |
| REAR SHOCK      | DT Swiss R232 ONE, size 190x45mm   |
| BOTTOM BRACKET  | SHIMANO BB-MT500PA, PressFit, shell 41x92mm  |
| HEADSET         | ACROS AZX-781S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings   |
| REAR AXLE       | SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black   |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO XT SW-M8250-IR, Di2, 12-speed   |
| REAR DERAILLEUR | SHIMANO XT RD-M8250, Shadow Plus Design |
| CRANKSET        | SHIMANO XT FC-M8220, 34T                |
| CASSETTE        | SHIMANO XT CS-M8200, 12-speed, 10-51T   |
| CHAIN           | SHIMANO DEORE CN-M6100                  |

### BRAKING SYSTEM

|             |  |
|-------------|--|
| BRAKE FRONT | SHIMANO XT M8200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT64, 180mm                 |
| BRAKE REAR  | SHIMANO XT M8200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT64, 160mm                 |

### WHEELS

|                |  |
|----------------|--|
| WHEELSET FRONT | DT Swiss XM 1700 SPLINE®, CL, 15x110mm, Tubeless Ready                 |
| WHEELSET REAR  | DT Swiss XM 1700 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready           |
| TYRE FRONT     | Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip   |
| TYRE REAR      | Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX |

### COCKPIT

|             |                                   |
|-------------|-----------------------------------|
| STEM        | ONE Race, Alloy, 31,8mm, -7°      |
| HANDLEBAR   | ONE Race, Alloy, 5mm rise, 31.8mm |
| GRIPS LEFT  | ONE Race, Lock-On                 |
| GRIPS RIGHT | ONE Race, Lock-On                 |

### PARTS

|                |                                       |
|----------------|---------------------------------------|
| SADDLE         | Fizik Ridon X5, Alloy                 |
| SEATPOST LEVER | SHIMANO SL-MT500-L, Seat post lever   |
| SEATPOST       | ONE Sport Dropper Post, Alloy, 30.9mm |
| SEATPOST CLAMP | ONE CC-080A, 34.9mm, Black            |

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19" (L)   | 21" (XL)  |
|--------------------------------|-----------|-----------|-----------|-----------|
| BB DROP (MM)                   | 42        | 42        | 42        | 42        |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482       | 533       |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 605       | 625       | 645       |
| STACK HEIGHT (MM)              | 583       | 593       | 602       | 611       |
| REACH (MM)                     | 439       | 460       | 478       | 496       |
| SEAT TUBE ANGLE                | 76,3°     | 76,3°     | 76,3°     | 76,3°     |
| HEAD TUBE ANGLE                | 66,5°     | 66,5°     | 66,5°     | 66,5°     |
| REAR CENTER (MM)               | 430       | 430       | 430       | 430       |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110       | 120       |
| WHEELBASE (MM)                 | 1153      | 1179      | 1200      | 1222      |
| STEM (MM)                      | 60        | 60        | 80        | 80        |
| HANDLEBAR (MM)                 | 760       | 760       | 760       | 760       |
| CRANKSET (MM)                  | 170       | 170       | 175       | 175       |
| SEATPOST (MM)                  | L408/T125 | L408/T125 | L458/T150 | L458/T150 |

## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | SU-01.2, Carbon MTB Race Pro, Advanced Race Geometry, Travel 110 mm, Integrated Cable routing, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 148x12 mm, Inner cable routing, Dropped seat post ready |
| SUSPENSION FORK | DT Swiss F232 ONE, Tapered, 15x110mm axle, 120mm travel  |
| REAR SHOCK      | DT Swiss R232 ONE, size 190x45mm   |
| BOTTOM BRACKET  | SHIMANO BB-MT500PA, PressFit, shell 41x92mm  |
| HEADSET         | ACROS AZX-781S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings   |
| REAR AXLE       | SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black   |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO DEORE SW-M6250-IR, Di2, 12-speed |
| REAR DERAILLEUR | SHIMANO DEORE RD-M6250-SGS               |
| CRANKSET        | SHIMANO SLX FC-M7120, Hollowtech II, 34T |
| CASSETTE        | SHIMANO DEORE CS-M6100, 12-speed, 10-51T |
| CHAIN           | SHIMANO DEORE CN-M6100                   |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO M6100, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT54, 180mm              |
| BRAKE REAR  | SHIMANO M6100, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT54, 160mm              |

### WHEELS

|                |  |
|----------------|--|
| WHEELSET FRONT | DT Swiss M 1900 SPLINE®, CL, 15x110mm, Tubeless Ready                  |
| WHEELSET REAR  | DT Swiss M 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready            |
| TYRE FRONT     | Schwalbe Racing Ray Performance, TL-Ready, 29x2.25", ADDIX SpeedGrip   |
| TYRE REAR      | Schwalbe Racing Ralph Performance, TwinSkin, TL-Ready, 29x2.25", ADDIX |

### COCKPIT

|             |                                   |
|-------------|-----------------------------------|
| STEM        | ONE Race, Alloy, 31,8mm, -7°      |
| HANDLEBAR   | ONE Race, Alloy, 5mm rise, 31.8mm |
| GRIPS LEFT  | ONE Race, Lock-On                 |
| GRIPS RIGHT | ONE Race, Lock-On                 |

### PARTS

|                |                                       |
|----------------|---------------------------------------|
| SADDLE         | Fizik Ridon X5, Alloy                 |
| SEATPOST LEVER | SHIMANO SL-MT500-L, Seat post lever   |
| SEATPOST       | ONE Sport Dropper Post, Alloy, 30.9mm |
| SEATPOST CLAMP | ONE CC-080A, 34.9mm, Black            |

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19" (L)   | 21" (XL)  |
|--------------------------------|-----------|-----------|-----------|-----------|
| BB DROP (MM)                   | 42        | 42        | 42        | 42        |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482       | 533       |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 605       | 625       | 645       |
| STACK HEIGHT (MM)              | 583       | 593       | 602       | 611       |
| REACH (MM)                     | 439       | 460       | 478       | 496       |
| SEAT TUBE ANGLE                | 76,3°     | 76,3°     | 76,3°     | 76,3°     |
| HEAD TUBE ANGLE                | 66,5°     | 66,5°     | 66,5°     | 66,5°     |
| REAR CENTER (MM)               | 430       | 430       | 430       | 430       |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110       | 120       |
| WHEELBASE (MM)                 | 1153      | 1179      | 1200      | 1222      |
| STEM (MM)                      | 60        | 60        | 80        | 80        |
| HANDLEBAR (MM)                 | 760       | 760       | 760       | 760       |
| CRANKSET (MM)                  | 170       | 170       | 175       | 175       |
| SEATPOST (MM)                  | L408/T125 | L408/T125 | L458/T150 | L458/T150 |

# XF 9.2 RC

Matte Carbon / White

MTB FULL-SUSPENSION / XF RC



# iXF 9.7

Matte Carbon

MTB FULL SUSPENSION | Light / iXF



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | SU-01, Carbon MTB Race Pro, Advanced Race Geometry, Travel 100 mm, Tapered Head Tube, BB92, 3D alloy one piece link, Carbon swingarm, SR dropout, Boost Thru Axle 12x148 mm, Inner cable routing, Dropped seat post ready |
| SUSPENSION FORK | RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel   |
| REAR SHOCK      | DT Swiss R232 ONE, size 190x45mm  |
| BOTTOM BRACKET  | SHIMANO BB-MT500PA, PressFit, shell 41x92mm   |
| HEADSET         | ACROS AZX-220 R4, ZS44/28.6 - ZS56/40, BlockLock 150°   |
| REAR AXLE       | SB01, TA12x171.5, M12xP1.5x15.5L, Black   |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO DEORE SL-M6100-IR, RAPIDFIRE Plus, 12-speed |
| REAR DERAILLEUR | SHIMANO DEORE RD-M6100, Shadow Plus Design          |
| CRANKSET        | SHIMANO FC-MT510, 34T                               |
| CASSETTE        | SHIMANO DEORE CS-M6100, 12-speed, 10-51T            |
| CHAIN           | SHIMANO DEORE CN-M6100                              |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT410, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT54, 180mm              |
| BRAKE REAR  | SHIMANO MT410, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT54, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready       |
| TYRE FRONT | Schwalbe Racing Ralph Performance, 29x2.25", ADDIX       |
| HUB REAR   | SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | WTB, KOM LIGHT TEAM i30, Disc, 32H, Tubeless Ready       |
| TYRE REAR  | Schwalbe Racing Ralph Performance, 29x2.25", ADDIX       |
| SPOKES     | SAPIM Leader, Stainless Black                            |
| NIPPLES    | SAPIM, Alloy   |

### COCKPIT

|             |                                   |
|-------------|-----------------------------------|
| STEM        | ONE Race, Alloy, 31,8mm, -7°      |
| HANDLEBAR   | ONE Race, Alloy, 5mm rise, 31.8mm |
| GRIPS LEFT  | ONE Race, Lock-On                 |
| GRIPS RIGHT | ONE Race, Lock-On                 |

### PARTS

|                |                                       |
|----------------|---------------------------------------|
| SADDLE         | Fizik Ridon X5, Alloy                 |
| SEATPOST LEVER | SHIMANO SL-MT500-L, Seat post lever   |
| SEATPOST       | ONE Sport Dropper Post, Alloy, 30.9mm |
| SEATPOST CLAMP | ONE CC-080A, 34.9mm, Black            |

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19.0" (L) | 21.0" (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 40        | 40        | 40        | 40         |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 584       | 610       | 630       | 650        |
| STACK HEIGHT (MM)              | 579       | 589       | 597       | 607        |
| REACH (MM)                     | 427       | 449       | 465       | 482        |
| SEAT TUBE ANGLE                | 74,9°     | 74,7°     | 74,6°     | 74,5°      |
| HEAD TUBE ANGLE                | 68°       | 68°       | 68°       | 68°        |
| REAR CENTER (MM)               | 428       | 428       | 428       | 428        |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110       | 120        |
| WHEELBASE (MM)                 | 1124      | 1149      | 1169      | 1189       |
| STEM (MM)                      | 60        | 60        | 80        | 80         |
| HANDLEBAR (MM)                 | 760       | 760       | 760       | 760        |
| CRANKSET (MM)                  | 170       | 175       | 175       | 175        |
| SEATPOST (MM)                  | L408/T125 | L408/T125 | L458/T150 | L458/T150  |

## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | BOSCH SX Performance, Battery CompactTube 400Wh |
| MAX. TORQUE         | 55Nm / 300%                                     |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)     |
| EN norm  | EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### E- BIKE PARTS

|         |                            |
|---------|----------------------------|
| MOTOR   | BOSCH Performance SX, 55Nm |
| CHARGER | BOSCH 2A                   |
| BATTERY | BOSCH CompactTube, 400Wh   |
| DISPLAY | BOSCH Mini Remote          |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | SU-E10-01, Carbon MTB DC; Advanced Down Country Geometry, Travel 140 mm, Integrated Cable routing, BB92, 3D one pice link, Carbon swingarm, UDH dropout, Boost Thru Axle 148x12 mm, Dropped seat post ready |
| SUSPENSION FORK | DT Swiss F535, Tapered, 15x110mm axle, 150mm travel   |
| REAR SHOCK      | DT Swiss R535, size 210x55mm  |
| HEADSET         | ACROS AZX-596S, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°, Stainless Bearings  |
| REAR AXLE       | SB01, TA12x175.5, M12xP1.0x14.5mm, Black  |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO SLX SL-M7100-IR, RAPIDFIRE Plus, 12-speed |
| REAR DERAILLEUR | SHIMANO XT RD-M8100, Shadow Plus Design           |
| CRANKSET        | ONE Race, Alloy                                   |
| CHAINRING       | ONE Race, 34T                                     |
| CASSETTE        | SHIMANO DEORE CS-M6100, 12-speed, 10-51T          |
| CHAIN           | SHIMANO DEORE CN-M6100                            |

### BRAKING SYSTEM

|             |  |
|-------------|--|
| BRAKE FRONT | SHIMANO XT M8220, 4 piston, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT64, 180mm                           |
| BRAKE REAR  | SHIMANO XT M8220, 4 piston, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT64, 180mm                           |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 15x110mm, Tubeless Ready          |
| WHEELSET REAR  | DT Swiss Hybrid MTB H 1900 SPLINE®, CL, 12x148mm, SH12, Tubeless Ready    |
| TYRE FRONT     | Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip |
| TYRE REAR      | Schwalbe Wicked Will Evo, SuperGround, TL-Easy, 29x2.40", ADDIX SpeedGrip |

### COCKPIT

|             |                            |
|-------------|----------------------------|
| STEM        | ONE Race, Alloy, 35mm, 0°  |
| HANDLEBAR   | ONE Alloy, 20mm rise, 35mm |
| GRIPS LEFT  | ONE Race, Lock-On          |
| GRIPS RIGHT | ONE Race, Lock-On          |

### PARTS

|                |                                       |
|----------------|---------------------------------------|
| SADDLE         | Fizik Aidon X5, Alloy                 |
| SEATPOST LEVER | SHIMANO SL-MT500-L, Seat post lever   |
| SEATPOST       | ONE Sport Dropper Post, Alloy, 30.9mm |
| SEATPOST CLAMP | ONE CC-080A, 34.9mm, Black            |

## GEOMETRY

| FRAME SIZE                     | 15.5" (S) | 17.5" (M) | 19" (L)   | 21" (XL)  |
|--------------------------------|-----------|-----------|-----------|-----------|
| BB DROP (MM)                   | 32        | 32        | 32        | 32        |
| SEAT TUBE LENGTH (MM)          | 393       | 420       | 440       | 460       |
| EFFECTIVE TOP TUBE LENGTH (MM) | 574       | 590       | 625       | 652       |
| STACK HEIGHT (MM)              | 606       | 605       | 636       | 645       |
| REACH (MM)                     | 450       | 465       | 490       | 515       |
| SEAT TUBE ANGLE                | 78°       | 78°       | 78°       | 78°       |
| HEAD TUBE ANGLE                | 64,5°     | 64,5°     | 64,5°     | 64,5°     |
| REAR CENTER (MM)               | 450       | 450       | 450       | 450       |
| HEAD TUBE LENGTH (MM)          | 90        | 100       | 110       | 120       |
| WHEELBASE (MM)                 | 1223      | 1239      | 1274      | 1301      |
| STEM (MM)                      | 45        | 45        | 45        | 45        |
| HANDLEBAR (MM)                 | 760       | 760       | 760       | 760       |
| CRANKSET (MM)                  | 165       | 165       | 165       | 170       |
| SEATPOST (MM)                  | L408/T125 | L458/T150 | L500/T170 | L500/T170 |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# XP 9.8

Matte Carbon / Dark Chrome

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

# XP 9.2

Matte Carbon / Dark Chrome

MTB HARDTAIL / XP



COMPUTER VISUALIZATION

## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm |
| SUSPENSION FORK | DT Swiss F232 ONE, Tapered, 15x110mm axle, 100mm travel  |
| BOTTOM BRACKET  | SHIMANO BB-MT500PA, PressFit, shell 41x92mm  |
| HEADSET         | ACROS AZX-781S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings   |
| REAR AXLE       | SB02-LT, TA12x175.5, M12x1,0x14.5L, Light, Black   |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO XT SW-M8250-IR, Di2, 12-speed   |
| REAR DERAILLEUR | SHIMANO XT RD-M8250, Shadow Plus Design |
| CRANKSET        | SHIMANO XT FC-M8200, 34T                |
| CASSETTE        | SHIMANO XT CS-M8200, 12-speed, 10-51T   |
| CHAIN           | SHIMANO XT CN-M8100                     |

### BRAKING SYSTEM

|             |  |
|-------------|--|
| BRAKE FRONT | SHIMANO XT M8200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO RT-CL800, 180mm                |
| BRAKE REAR  | SHIMANO XT M8200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO RT-CL800, 160mm                |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss XRC 1700 SPLINE®, Carbon, CL, 15x110mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss XRC 1700 SPLINE®, Carbon, CL, 12x148mm, SH12, Tubeless Ready |
| TYRE FRONT     | Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed    |
| TYRE REAR      | Schwalbe Racing Ric Evo, TL-Easy, SuperRace, 29x2.25", ADDIX Speed    |

### COCKPIT

|             |                                   |
|-------------|-----------------------------------|
| STEM        | ONE Race, Alloy, 31,8mm, -7°      |
| HANDLEBAR   | ONE Race, Alloy, 5mm rise, 31.8mm |
| GRIPS LEFT  | ONE Race, Lock-On                 |
| GRIPS RIGHT | ONE Race, Lock-On                 |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Ridon X5, Alloy      |
| SEATPOST       | ONE Race, Carbon, 27.2mm   |
| SEATPOST CLAMP | ONE CC-080A, 31,8mm, Black |

## GEOMETRY

| FRAME SIZE                     | 13,5" (XS) | 15,5" (S) | 17,5" (M) | 19" (L) | 21" (XL) |
|--------------------------------|------------|-----------|-----------|---------|----------|
| BB DROP (MM)                   | 57         | 57        | 57        | 57      | 57       |
| SEAT TUBE LENGTH (MM)          | 30         | 393       | 431       | 482     | 533      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 565        | 590       | 615       | 635     | 645      |
| STACK HEIGHT (MM)              | 599        | 599       | 603       | 613     | 622      |
| REACH (MM)                     | 415        | 435       | 455       | 475     | 495      |
| SEAT TUBE ANGLE                | 75,9°      | 75,5°     | 75,2°     | 75,4°   | 76,4°    |
| HEAD TUBE ANGLE                | 66,5°      | 66,5°     | 66,5°     | 66,5°   | 66,5°    |
| REAR CENTER (MM)               | 430        | 430       | 430       | 430     | 430      |
| HEAD TUBE LENGTH (MM)          | 90         | 90        | 95        | 105     | 115      |
| WHEELBASE (MM)                 | 1127       | 1147      | 1169      | 1193    | 1217     |
| STEM (MM)                      | 60         | 60        | 60        | 80      | 80       |
| HANDLEBAR (MM)                 | 760        | 760       | 760       | 760     | 760      |
| CRANKSET (MM)                  | 165        | 170       | 170       | 175     | 175      |

## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Carbon MTB Race Pro Mid Modulus, Advanced Race Geometry, Integrated Cable Routing, BB92, SR dropout, Boost Thru Axle 148x12 mm |
| SUSPENSION FORK | RockShox Recon Silver RL R, Tapered, SoloAir, 15x110mm axle, 100mm travel  |
| BOTTOM BRACKET  | SHIMANO BB-MT500PA, PressFit, shell 41x92mm  |
| HEADSET         | ACROS AZX-781, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°  |
| REAR AXLE       | SB01, TA12x175.5, M12xP1.0x14.5mm, Black   |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO DEORE SW-M6250-IR, Di2, 12-speed |
| REAR DERAILLEUR | SHIMANO DEORE RD-M6250-SGS               |
| CRANKSET        | SHIMANO FC-MT510, 32T                    |
| CASSETTE        | SHIMANO DEORE CS-M6100, 12-speed, 10-51T |
| CHAIN           | SHIMANO DEORE CN-M6100                   |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT410, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT54, 180mm              |
| BRAKE REAR  | SHIMANO MT410, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT54, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | WTB, KOM LIGHT TEAM i25, Disc, 32H, Tubeless Ready       |
| TYRE FRONT | Schwalbe Racing Ralph Performance, 29x2.25", ADDIX       |
| HUB REAR   | SHIMANO FH-TC500-MS-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | WTB, KOM LIGHT TEAM i25, Disc, 32H, Tubeless Ready       |
| TYRE REAR  | Schwalbe Racing Ralph Performance, 29x2.25", ADDIX       |
| SPOKES     | SAPIM Laser/Race, Stainless Black                        |
| NIPPLES    | SAPIM, Alloy   |

### COCKPIT

|             |                                   |
|-------------|-----------------------------------|
| STEM        | ONE Race, Alloy, 31,8mm, -7°      |
| HANDLEBAR   | ONE Race, Alloy, 5mm rise, 31.8mm |
| GRIPS LEFT  | ONE Sport, Lock-On                |
| GRIPS RIGHT | ONE Sport, Lock-On                |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Ridon X5, Alloy      |
| SEATPOST       | ONE Race, Alloy, 27.2mm    |
| SEATPOST CLAMP | ONE CC-080A, 31,8mm, Black |

## GEOMETRY

| FRAME SIZE                     | 13,5" (XS) | 15,5" (S) | 17,5" (M) | 19" (L) | 21" (XL) |
|--------------------------------|------------|-----------|-----------|---------|----------|
| BB DROP (MM)                   | 57         | 57        | 57        | 57      | 57       |
| SEAT TUBE LENGTH (MM)          | 30         | 393       | 431       | 482     | 533      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 565        | 590       | 615       | 635     | 645      |
| STACK HEIGHT (MM)              | 599        | 599       | 603       | 613     | 622      |
| REACH (MM)                     | 415        | 435       | 455       | 475     | 495      |
| SEAT TUBE ANGLE                | 75,9°      | 75,5°     | 75,2°     | 75,4°   | 76,4°    |
| HEAD TUBE ANGLE                | 66,5°      | 66,5°     | 66,5°     | 66,5°   | 66,5°    |
| REAR CENTER (MM)               | 430        | 430       | 430       | 430     | 430      |
| HEAD TUBE LENGTH (MM)          | 90         | 90        | 95        | 105     | 115      |
| WHEELBASE (MM)                 | 1127       | 1147      | 1169      | 1193    | 1217     |
| STEM (MM)                      | 60         | 60        | 60        | 80      | 80       |
| HANDLEBAR (MM)                 | 760        | 760       | 760       | 760     | 760      |
| CRANKSET (MM)                  | 170        | 170       | 170       | 175     | 175      |

# iXP 6.5

Gloss Grey



# eXP 6.5

Matte Dark Chrome / Black

eMTB HARDTAIL / eXP



## SPECIFICATION

| BASE INFO           |   |
|---------------------|---|
| E-SYSTEM            | BOSCH SX Performance, Battery CompactTube 400Wh |
| MAX. TORQUE         | 55Nm / 300%                                     |
| SUPPORT UP TO SPEED | 25km/h  |

| ISO AND EN NORM |  |
|-----------------|--|
| ISO norm        | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)      |
| EN norm         | EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

| E- BIKE PARTS |                            |
|---------------|----------------------------|
| MOTOR         | BOSCH Performance SX, 55Nm |
| CHARGER       | BOSCH 2A                   |
| BATTERY       | BOSCH CompactTube, 400Wh   |
| DISPLAY       | BOSCH Kiox 300             |

| FRAMESET        |   |
|-----------------|---|
| FRAME           | SU-E41-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 100mm travel  |
| HEADSET         | ACROS AZX-596, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°   |
| REAR AXLE       | SB02, TA12x171.5, M12xP1.0x14.5mm, Black  |

| DRIVETRAIN      |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed |
| REAR DERAILLEUR | SHIMANO CUES RD-U6000, Shadow Plus Design           |
| CRANKSET        | ONE Race, Alloy                                     |
| CHAINRING       | ONE Race, 34T                                       |
| CASSETTE        | SHIMANO CUES CS-LG400, 11-speed, 11-50T             |
| CHAIN           | SHIMANO CN-LG500                                    |

| BRAKING SYSTEM |                                     |
|----------------|-------------------------------------|
| BRAKE FRONT    | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT    | SHIMANO SM-RT10, 180mm              |
| BRAKE REAR     | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR     | SHIMANO SM-RT10, 180mm              |

| WHEELS     |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | STARS J30D, Disc, 32H                                    |
| TYRE FRONT | Schwalbe Smart Sam, KevlarGuard, 29x2.40"                |
| HUB REAR   | SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | STARS J30D, Disc, 32H                                    |
| TYRE REAR  | Schwalbe Smart Sam, KevlarGuard, 29x2.40"                |
| SPOKES     | SAPIM Leader, Stainless Black                            |
| NIPPLES    | SAPIM, Brass   |

| COCKPIT     |                            |
|-------------|----------------------------|
| STEM        | ONE Race, Alloy, 35mm, 0°  |
| HANDLEBAR   | ONE Alloy, 20mm rise, 35mm |
| GRIPS LEFT  | ONE Sport Ergo, Lock-On    |
| GRIPS RIGHT | ONE Sport Ergo, Lock-On    |

| PARTS          |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |

## GEOMETRY

| FRAME SIZE                     | 14" (XS) | 16" (S) | 18" (M) | 20" (L) | 22" (XL) |
|--------------------------------|----------|---------|---------|---------|----------|
| BB DROP (MM)                   | 60       | 60      | 60      | 60      | 60       |
| SEAT TUBE LENGTH (MM)          | 365      | 406     | 457     | 508     | 559      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 550      | 570     | 590     | 610     | 630      |
| STACK HEIGHT (MM)              | 632      | 642     | 651     | 660     | 670      |
| REACH (MM)                     | 369      | 386     | 403     | 421     | 438      |
| SEAT TUBE ANGLE                | 74°      | 74°     | 74°     | 74°     | 74°      |
| HEAD TUBE ANGLE                | 69°      | 69°     | 69°     | 69°     | 69°      |
| REAR CENTER (MM)               | 450      | 450     | 450     | 450     | 450      |
| HEAD TUBE LENGTH (MM)          | 110      | 120     | 130     | 140     | 150      |
| WHEELBASE (MM)                 | 1081     | 1102    | 1123    | 1144    | 1165     |
| STEM (MM)                      | 45       | 45      | 45      | 45      | 45       |
| HANDLEBAR (MM)                 | 760      | 760     | 760     | 760     | 760      |
| CRANKSET (MM)                  | 160      | 160     | 165     | 170     | 170      |
| SEATPOST (MM)                  | 350      | 350     | 350     | 350     | 350      |

## SPECIFICATION

| BASE INFO           |   |
|---------------------|---|
| E-SYSTEM            | BOSCH CX Performance, Battery PowerTube 600Wh |
| DISTANCE            | 150km   |
| MAX. TORQUE         | 85Nm / 340%                                   |
| SUPPORT UP TO SPEED | 25km/h  |

| ISO AND EN NORM |   |
|-----------------|---|
| ISO norm        | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)     |
| EN norm         | EN 17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

| E- BIKE PARTS |                            |
|---------------|----------------------------|
| MOTOR         | BOSCH Performance CX, 85Nm |
| CHARGER       | BOSCH 2A                   |
| BATTERY       | BOSCH PowerTube, 600Wh     |
| DISPLAY       | BOSCH Kiox 300             |

| FRAMESET        |  |
|-----------------|--|
| FRAME           | SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready |
| SUSPENSION FORK | RockShox Judy Silver TK, Tapered, SoloAir, 15x110mm axle, 120mm travel   |
| HEADSET         | ACROS AZX-596, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°  |
| REAR AXLE       | SB02, TA12x171.5, M12xP1.0x14.5mm, Black   |

| DRIVETRAIN      |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO CUES SL-U6000-11R, RAPIDFIRE Plus, 11-speed |
| REAR DERAILLEUR | SHIMANO XT RD-M8130, Shadow Plus Design             |
| CRANKSET        | ONE Race, Alloy                                     |
| CHAINRING       | ONE Race, 34T                                       |
| CASSETTE        | SHIMANO CUES CS-LG400, 11-speed, 11-50T             |
| CHAIN           | SHIMANO CN-LG500                                    |

| BRAKING SYSTEM |   |
|----------------|---|
| BRAKE FRONT    | SHIMANO MT420, 4 piston, hydraulic disc brake |
| ROTOR FRONT    | SHIMANO SM-RT30, 203MM                        |
| BRAKE REAR     | SHIMANO MT420, 4 piston, hydraulic disc brake |
| ROTOR REAR     | SHIMANO SM-RT30, 180mm                        |

| WHEELS     |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | STARS J30D, Disc, 32H                                    |
| TYRE FRONT | Schwalbe Wicked Will Performance, 29x2.40", ADDIX        |
| HUB REAR   | SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | STARS J30D, Disc, 32H                                    |
| TYRE REAR  | Schwalbe Wicked Will Performance, 29x2.40", ADDIX        |
| SPOKES     | SAPIM Leader, Stainless Black                            |
| NIPPLES    | SAPIM, Brass   |

| COCKPIT     |                            |
|-------------|----------------------------|
| STEM        | ONE Race, Alloy, 35mm, 0°  |
| HANDLEBAR   | ONE Alloy, 20mm rise, 35mm |
| GRIPS LEFT  | ONE Sport Ergo, Lock-On    |
| GRIPS RIGHT | ONE Sport Ergo, Lock-On    |

| PARTS          |                                       |
|----------------|---------------------------------------|
| SADDLE         | Selle Royal Vivo                      |
| SEATPOST LEVER | SHIMANO SL-MT500-L, Seat post lever   |
| SEATPOST       | ONE Sport Dropper Post, Alloy, 30,9mm |
| SEATPOST CLAMP | ONE, 34,9mm, Black Matte              |

## GEOMETRY

| FRAME SIZE                     | 15,5" (S) | 17,5" (M) | 19" (L)   | 21" (XL)  |
|--------------------------------|-----------|-----------|-----------|-----------|
| BB DROP (MM)                   | 56        | 56        | 56        | 56        |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482       | 533       |
| EFFECTIVE TOP TUBE LENGTH (MM) | 592       | 612       | 632       | 642       |
| STACK HEIGHT (MM)              | 638       | 638       | 638       | 656       |
| REACH (MM)                     | 460       | 459       | 479       | 500       |
| SEAT TUBE ANGLE                | 78°       | 77°       | 77°       | 77°       |
| HEAD TUBE ANGLE                | 66°       | 66°       | 66°       | 66°       |
| REAR CENTER (MM)               | 442       | 442       | 442       | 442       |
| HEAD TUBE LENGTH (MM)          | 120       | 120       | 120       | 140       |
| WHEELBASE (MM)                 | 1215      | 1215      | 1235      | 1264      |
| STEM (MM)                      | 45        | 45        | 45        | 45        |
| HANDLEBAR (MM)                 | 760       | 760       | 760       | 760       |
| CRANKSET (MM)                  | 165       | 165       | 165       | 170       |
| SEATPOST (MM)                  | L408/T125 | L458/T150 | L500/T170 | L500/T170 |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# eXP 6.3

Gloss Grey / Red

eMTB HARDTAIL / eXP



# XC 6.9

Matte Dark Red / Red

MTB HARDTAIL / XC



## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | BOSCH PX Performance, Battery PowerTube 600Wh |
| DISTANCE            | 150km   |
| MAX. TORQUE         | 85Nm / 340%                                   |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)    |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### E- BIKE PARTS

|         |                            |
|---------|----------------------------|
| MOTOR   | BOSCH Performance PX, 85Nm |
| CHARGER | BOSCH 2A                   |
| BATTERY | BOSCH PowerTube, 600Wh     |
| DISPLAY | BOSCH Intuiva 100          |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | SU-E40-01, Alu X6 Ultralite, Advanced eMTB Geometry, Integrated battery, SR dropout, Boost 12x148 mm, Inner cable routing, Dropper seat post ready |
| SUSPENSION FORK | SR Suntour XCR32, Tapered, 15x110mm axle, 120mm travel   |
| HEADSET         | ACROS AZX-596, ICR, ZS56/28.6 - ZS56/40, BlockLock 120°  |
| REAR AXLE       | SB02, TA12x171.5, M12xP1.0x14.5mm, Black   |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed |
| REAR DERAILLEUR | SHIMANO CUES RD-U4000, Shadow Design              |
| CRANKSET        | ONE Race, Alloy                                   |
| CHAINRING       | ONE Race, 34T                                     |
| CASSETTE        | SHIMANO CUES CS-LG300, 9-speed, 11-46T            |
| CHAIN           | SHIMANO CN-LG500                                  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 180mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 180mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | STARS J30D, Disc, 32H                                    |
| TYRE FRONT | Schwalbe Hurricane Performance, 29x2.25, ADDIX           |
| HUB REAR   | SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | STARS J30D, Disc, 32H                                    |
| TYRE REAR  | Schwalbe Hurricane Performance, 29x2.25, ADDIX           |
| SPOKES     | SAPIM Galvanized Black                                   |
| NIPPLES    | SAPIM, Brass   |

### COCKPIT

|             |                            |
|-------------|----------------------------|
| STEM        | ONE Race, Alloy, 35mm, 0°  |
| HANDLEBAR   | ONE Alloy, 20mm rise, 35mm |
| GRIPS LEFT  | ONE Sport Ergo, Lock-On    |
| GRIPS RIGHT | ONE Sport Ergo, Lock-On    |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Race, Alloy, 30,9mm                             |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |

## GEOMETRY

| FRAME SIZE                     | 15,5" (S) | 17,5" (M) | 19" (L) | 21" (XL) |
|--------------------------------|-----------|-----------|---------|----------|
| BB DROP (MM)                   | 56        | 56        | 56      | 56       |
| SEAT TUBE LENGTH (MM)          | 393       | 431       | 482     | 533      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 592       | 612       | 632     | 642      |
| STACK HEIGHT (MM)              | 638       | 638       | 638     | 656      |
| REACH (MM)                     | 460       | 459       | 479     | 500      |
| SEAT TUBE ANGLE                | 78°       | 77°       | 77°     | 77°      |
| HEAD TUBE ANGLE                | 66°       | 66°       | 66°     | 66°      |
| REAR CENTER (MM)               | 442       | 442       | 442     | 442      |
| HEAD TUBE LENGTH (MM)          | 120       | 120       | 120     | 140      |
| WHEELBASE (MM)                 | 1215      | 1215      | 1235    | 1264     |
| STEM (MM)                      | 45        | 45        | 45      | 45       |
| HANDLEBAR (MM)                 | 760       | 760       | 760     | 760      |
| CRANKSET (MM)                  | 165       | 165       | 165     | 170      |

## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                        |   |
|------------------------|---|
| FRAME                  | Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout, |
| SUSPENSION FORK        | RST Aerial, 1-1/8", 120mm travel  |
| BOTTOM BRACKET HEADSET | SHIMANO, Cartridge Bearing<br>ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30  |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO DEORE SL-M5100-R, RAPIDFIRE Plus, 11-speed |
| REAR DERAILLEUR | SHIMANO DEORE RD-M5100, Shadow Plus Design         |
| CRANKSET        | SHIMANO FC-MT5100-1, 32T                           |
| CASSETTE        | SHIMANO DEORE CS-M5100, 11-speed, 11-51T           |
| CHAIN           | KMC X11 Grey                                       |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 180mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type     |
| RIM FRONT  | STARS J25D, Disc, 32H                            |
| TYRE FRONT | CST Jack Rabbit, 29x2.25"                        |
| HUB REAR   | SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type |
| RIM REAR   | STARS J25D, Disc, 32H                            |
| TYRE REAR  | CST Jack Rabbit, 29x2.25"                        |
| SPOKES     | SAPIM Galvanized Black                           |
| NIPPLES    | SAPIM, Brass                                     |

### COCKPIT

|             |                               |
|-------------|-------------------------------|
| STEM        | ONE Sport, Alloy, 31.8mm, -8° |
| HANDLEBAR   | ONE Alloy, 12mm rise, 31.8mm  |
| GRIPS LEFT  | ONE Sport, Lock-On            |
| GRIPS RIGHT | ONE Sport, Lock-On            |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-610  |

## GEOMETRY

| FRAME SIZE                     | 16" (S) | 18" (M) | 20" (L) | 22" (XL) |
|--------------------------------|---------|---------|---------|----------|
| BB DROP (MM)                   | 60      | 60      | 60      | 60       |
| SEAT TUBE LENGTH (MM)          | 406     | 457     | 508     | 559      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580     | 605     | 625     | 635      |
| STACK HEIGHT (MM)              | 608     | 617     | 617     | 636      |
| REACH (MM)                     | 423     | 445     | 465     | 471      |
| SEAT TUBE ANGLE                | 75,5°   | 75,5°   | 75,5°   | 75,5°    |
| HEAD TUBE ANGLE                | 67°     | 67°     | 67°     | 67°      |
| REAR CENTER (MM)               | 420     | 420     | 420     | 420      |
| HEAD TUBE LENGTH (MM)          | 90      | 100     | 100     | 120      |
| WHEELBASE (MM)                 | 1143    | 1170    | 1190    | 1203     |
| STEM (MM)                      | 70      | 70      | 90      | 90       |
| HANDLEBAR (MM)                 | 740     | 740     | 740     | 740      |
| CRANKSET (MM)                  | 170     | 175     | 175     | 175      |



# XC 6.8

Matte Sand

MTB HARDTAIL / XC



# XC 6.7

Gloss Grey / Orange

MTB HARDTAIL / XC



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout, |
| SUSPENSION FORK | RST Aerial, 1-1/8", 100mm travel  |
| BOTTOM BRACKET  | SHIMANO, Cartridge Bearing  |
| HEADSET         | ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO DEORE SL-M5100-L, RAPIDFIRE Plus, 2-speed  |
| SHIFTERS RIGHT   | SHIMANO DEORE SL-M5100-R, RAPIDFIRE Plus, 11-speed |
| FRONT DERAILLEUR | SHIMANO DEORE FD-M5100-M, Side Swing, Front Pull   |
| REAR DERAILLEUR  | SHIMANO DEORE RD-M4120, Shadow Design              |
| CRANKSET         | SHIMANO FC-M5100-2, 36-26T                         |
| CASSETTE         | SHIMANO DEORE CS-M5100, 11-speed, 11-42T           |
| CHAIN            | KMC X11 Grey                                       |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 180mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type     |
| RIM FRONT  | STARS J25D, Disc, 32H                            |
| TYRE FRONT | CST Jack Rabbit, 29x2.25"                        |
| HUB REAR   | SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type |
| RIM REAR   | STARS J25D, Disc, 32H                            |
| TYRE REAR  | CST Jack Rabbit, 29x2.25"                        |
| SPOKES     | SAPIM Galvanized Black                           |
| NIPPLES    | SAPIM, Brass                                     |

### COCKPIT

|             |                               |
|-------------|-------------------------------|
| STEM        | ONE Sport, Alloy, 31.8mm, -8° |
| HANDLEBAR   | ONE Alloy, 12mm rise, 31.8mm  |
| GRIPS LEFT  | ONE Sport, Lock-On            |
| GRIPS RIGHT | ONE Sport, Lock-On            |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-610  |

## GEOMETRY

| FRAME SIZE                     | 16" (S) | 18" (M) | 20" (L) | 22" (XL) |
|--------------------------------|---------|---------|---------|----------|
| BB DROP (MM)                   | 60      | 60      | 60      | 60       |
| SEAT TUBE LENGTH (MM)          | 406     | 457     | 508     | 559      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580     | 605     | 625     | 635      |
| STACK HEIGHT (MM)              | 608     | 617     | 617     | 636      |
| REACH (MM)                     | 423     | 445     | 465     | 471      |
| SEAT TUBE ANGLE                | 75,5°   | 75,5°   | 75,5°   | 75,5°    |
| HEAD TUBE ANGLE                | 67°     | 67°     | 67°     | 67°      |
| REAR CENTER (MM)               | 420     | 420     | 420     | 420      |
| HEAD TUBE LENGTH (MM)          | 90      | 100     | 100     | 120      |
| WHEELBASE (MM)                 | 1143    | 1170    | 1190    | 1203     |
| STEM (MM)                      | 70      | 70      | 90      | 90       |
| HANDLEBAR (MM)                 | 740     | 740     | 740     | 740      |
| CRANKSET (MM)                  | 170     | 175     | 175     | 175      |

## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout, |
| SUSPENSION FORK | RST Aerial, 1-1/8", 100mm travel  |
| BOTTOM BRACKET  | SHIMANO BB-MT501, BSA, shell 68/73mm  |
| HEADSET         | ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO DEORE SL-M5100-L, RAPIDFIRE Plus, 2-speed  |
| SHIFTERS RIGHT   | SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed |
| FRONT DERAILLEUR | SHIMANO DEORE FD-M4100-M, Side Swing, Front Pull   |
| REAR DERAILLEUR  | SHIMANO DEORE RD-M4120, Shadow Design              |
| CRANKSET         | ONE Race, Alloy, 36-26T                            |
| CASSETTE         | SHIMANO DEORE CS-M4100, 10-speed, 11-42T           |
| CHAIN            | KMC X10  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type     |
| RIM FRONT  | STARS J25D, Disc, 32H                            |
| TYRE FRONT | CST Jack Rabbit, 29x2.25"                        |
| HUB REAR   | SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type |
| RIM REAR   | STARS J25D, Disc, 32H                            |
| TYRE REAR  | CST Jack Rabbit, 29x2.25"                        |
| SPOKES     | SAPIM Galvanized Black                           |
| NIPPLES    | SAPIM, Brass                                     |

### COCKPIT

|             |                               |
|-------------|-------------------------------|
| STEM        | ONE Sport, Alloy, 31.8mm, -8° |
| HANDLEBAR   | ONE Alloy, 12mm rise, 31.8mm  |
| GRIPS LEFT  | ONE Sport, Lock-On            |
| GRIPS RIGHT | ONE Sport, Lock-On            |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-610  |

## GEOMETRY

| FRAME SIZE                     | 16" (S) | 18" (M) | 20" (L) | 22" (XL) |
|--------------------------------|---------|---------|---------|----------|
| BB DROP (MM)                   | 60      | 60      | 60      | 60       |
| SEAT TUBE LENGTH (MM)          | 406     | 457     | 508     | 559      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580     | 605     | 625     | 635      |
| STACK HEIGHT (MM)              | 608     | 617     | 617     | 636      |
| REACH (MM)                     | 423     | 445     | 465     | 471      |
| SEAT TUBE ANGLE                | 75,5°   | 75,5°   | 75,5°   | 75,5°    |
| HEAD TUBE ANGLE                | 67°     | 67°     | 67°     | 67°      |
| REAR CENTER (MM)               | 420     | 420     | 420     | 420      |
| HEAD TUBE LENGTH (MM)          | 90      | 100     | 100     | 120      |
| WHEELBASE (MM)                 | 1143    | 1170    | 1190    | 1203     |
| STEM (MM)                      | 70      | 70      | 90      | 90       |
| HANDLEBAR (MM)                 | 740     | 740     | 740     | 740      |
| CRANKSET (MM)                  | 170     | 175     | 175     | 175      |
| SEATPOST (MM)                  | 350     | 350     | 350     | 350      |

# XC 6.5

Matte Black / Chrome

MTB HARDTAIL / XC



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 MTB bicycles  |
| EN norm  | EN17406 Condition 3 For rough Off-Road riding and jumps less than 60cm |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | Alu 6061 T6 Double Butted, Smooth Welding, Sport Geometry, Geometry, Integrated Cable Routing, BB BSA 73 mm, IDK dropout, |
| SUSPENSION FORK | RST Blaze, 1-1/8", 120mm travel   |
| BOTTOM BRACKET  | SHIMANO, Cartridge Bearing  |
| HEADSET         | ONE CHH1505, 1-1/8", ZS44/28.6 - ZS56/30  |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO DEORE SL-M4100-R, RAPIDFIRE Plus, 10-speed |
| REAR DERAILLEUR | SHIMANO DEORE RD-M4120, Shadow Design              |
| CRANKSET        | SHIMANO FC-MT5100-1, 32T                           |
| CASSETTE        | SHIMANO DEORE CS-M4100, 10-speed, 11-42T           |
| CHAIN           | KMC X10  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-QC300, 32H, CL, M9X100mm, QR Type     |
| RIM FRONT  | STARS J25D, Disc, 32H                            |
| TYRE FRONT | CST Jack Rabbit, 29x2.25"                        |
| HUB REAR   | SHIMANO FH-QC300-HM, 32H, CL, M10X135mm, QR Type |
| RIM REAR   | STARS J25D, Disc, 32H                            |
| TYRE REAR  | CST Jack Rabbit, 29x2.25"                        |
| SPOKES     | SAPIM Galvanized Black                           |
| NIPPLES    | SAPIM, Brass                                     |

### COCKPIT

|             |                               |
|-------------|-------------------------------|
| STEM        | ONE Sport, Alloy, 31.8mm, -8° |
| HANDLEBAR   | ONE Alloy, 12mm rise, 31.8mm  |
| GRIPS LEFT  | ONE Sport, Lock-On            |
| GRIPS RIGHT | ONE Sport, Lock-On            |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-610  |

## GEOMETRY

| FRAME SIZE                     | 16" (S) | 18" (M) | 20" (L) | 22" (XL) |
|--------------------------------|---------|---------|---------|----------|
| BB DROP (MM)                   | 60      | 60      | 60      | 60       |
| SEAT TUBE LENGTH (MM)          | 406     | 457     | 508     | 559      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580     | 605     | 625     | 635      |
| STACK HEIGHT (MM)              | 608     | 617     | 617     | 636      |
| REACH (MM)                     | 423     | 445     | 465     | 471      |
| SEAT TUBE ANGLE                | 75,5°   | 75,5°   | 75,5°   | 75,5°    |
| HEAD TUBE ANGLE                | 67°     | 67°     | 67°     | 67°      |
| REAR CENTER (MM)               | 420     | 420     | 420     | 420      |
| HEAD TUBE LENGTH (MM)          | 90      | 100     | 100     | 120      |
| WHEELBASE (MM)                 | 1143    | 1170    | 1190    | 1203     |
| STEM (MM)                      | 70      | 70      | 90      | 90       |
| HANDLEBAR (MM)                 | 740     | 740     | 740     | 740      |
| CRANKSET (MM)                  | 170     | 175     | 175     | 175      |
| SEATPOST (MM)                  | 350     | 350     | 350     | 350      |



\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# XR 9.9 GR

Matte Carbon / Gloss Red

ROAD & GRAVEL / GRAVEL



## SPECIFICATION

| ISO AND EN NORM |   |
|-----------------|---|
| ISO norm        | ISO 4210-2 Road Racing bicycles   |
| EN norm         | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

| FRAMESET       |  |
|----------------|--|
| FRAME          | SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready. |
| FORK           | XR Hi Modulus Carbon Fork  |
| BOTTOM BRACKET | SRAM DUB ROAD WIDE, PressFit, shell 41x86.5 mm   |
| HEADSET        | ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings   |
| FRONT AXLE     | SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black   |
| REAR AXLE      | SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black  |

| DRIVETRAIN      |   |
|-----------------|---|
| SHIFTERS LEFT   | SRAM RED AXS, electronic shifter        |
| SHIFTERS RIGHT  | SRAM RED AXS, electronic shifter        |
| REAR DERAILLEUR | SRAM RED XPLR AXS, 13 speed             |
| CRANKSET        | SRAM RED XPLR, DUB WIDE, 44T            |
| CASSETTE        | SRAM RED XPLR XG-1391, 13-speed, 10-46T |
| CHAIN           | SRAM RED, Flattop                       |

| BRAKING SYSTEM |                                    |
|----------------|------------------------------------|
| BRAKE FRONT    | SRAM RED AXS, hydraulic disc brake |
| ROTOR FRONT    | SRAM Paceline X, 160mm             |
| BRAKE REAR     | SRAM RED AXS, hydraulic disc brake |
| ROTOR REAR     | SRAM Paceline X, 140mm             |

| WHEELS         |  |
|----------------|--|
| WHEELSET FRONT | DT Swiss GRC 1600, Carbon, CL, 12x100mm, Tubeless Ready      |
| WHEELSET REAR  | DT Swiss GRC 1600, Carbon, CL, 12x142mm, XDR, Tubeless Ready |
| TYRE FRONT     | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX   |
| TYRE REAR      | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX   |

| COCKPIT    |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

| PARTS          |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Vento Argo R5, Alloy |
| SEATPOST       | ONE Aero Carbon            |
| SEATPOST CLAMP | Frame Integrated Clamp     |

## GEOMETRY

| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) | 610mm (XXL) |
|--------------------------------|------------|-----------|-----------|-----------|------------|-------------|
| BB DROP (MM)                   | 77         | 77        | 77        | 77        | 77         | 77          |
| SEAT TUBE LENGTH (MM)          | 440        | 462       | 482       | 502       | 522        | 552         |
| EFFECTIVE TOP TUBE LENGTH (MM) | 525        | 532       | 545       | 569       | 591        | 610         |
| STACK HEIGHT (MM)              | 517        | 537       | 557       | 578       | 597        | 605         |
| REACH (MM)                     | 370        | 376       | 380       | 392       | 408        | 417         |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        | 72,5°       |
| HEAD TUBE ANGLE                | 71°        | 71°       | 71,5°     | 71,5°     | 72°        | 72°         |
| REAR CENTER (MM)               | 415        | 415       | 415       | 415       | 415        | 415         |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        | 200         |
| WHEELBASE (MM)                 | 994        | 995       | 1000      | 1016      | 1034       | 1048        |
| HANDLEBAR (MM)                 | 380/70     | 380/70    | 420/90    | 420/90    | 440/100    | 440/100     |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172,5     | 172,5      | 175         |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        | 400         |

# XR 9.5 GR

Matte Green Grey / Green

ROAD & GRAVEL / GRAVEL



## SPECIFICATION

| ISO AND EN NORM |   |
|-----------------|---|
| ISO norm        | ISO 4210-2 Road Racing bicycles   |
| EN norm         | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

| FRAMESET       |   |
|----------------|---|
| FRAME          | SU-52-01, Carbon XR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready. |
| FORK           | XR Mid Modulus Carbon Fork  |
| BOTTOM BRACKET | SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm   |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS   |
| FRONT AXLE     | SB02, TA12x119, M12xP1.5x8.5L, Black  |
| REAR AXLE      | SB02, TA12x171.5, M12xP1.0x14.5mm, Black  |

| DRIVETRAIN      |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO GRX RX610, 12-speed              |
| REAR DERAILLEUR | SHIMANO GRX RD-RX822, Shadow Plus Design |
| CRANKSET        | SHIMANO GRX FC-RX610, 40T                |
| CASSETTE        | SHIMANO SLX CS-M7101, 12-speed, 10-45T   |
| CHAIN           | SHIMANO DEORE CN-M6100                   |

| BRAKING SYSTEM |   |
|----------------|---|
| BRAKE FRONT    | SHIMANO GRX RX610, hydraulic disc brake |
| ROTOR FRONT    | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR     | SHIMANO GRX RX610, hydraulic disc brake |
| ROTOR REAR     | SHIMANO SM-RT70, 140mm                  |

| WHEELS         |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss G 1800 SPLINE®, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss G 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready |
| TYRE FRONT     | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX  |
| TYRE REAR      | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX  |

| COCKPIT    |  |
|------------|--|
| STEM       | ONE Race ICR, Alloy, 31,8mm, -7°                                     |
| HANDLEBAR  | ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6° |
| GRIPS LEFT | ONE Handlebar Tape   |

| PARTS          |                        |
|----------------|------------------------|
| SADDLE         | Selle Royal Gravel     |
| SEATPOST       | ONE Aero Carbon        |
| SEATPOST CLAMP | Frame Integrated Clamp |

## GEOMETRY

| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) | 610mm (XXL) |
|--------------------------------|------------|-----------|-----------|-----------|------------|-------------|
| BB DROP (MM)                   | 77         | 77        | 77        | 77        | 77         | 77          |
| SEAT TUBE LENGTH (MM)          | 440        | 462       | 482       | 502       | 522        | 552         |
| EFFECTIVE TOP TUBE LENGTH (MM) | 525        | 532       | 545       | 569       | 591        | 610         |
| STACK HEIGHT (MM)              | 517        | 537       | 557       | 578       | 597        | 605         |
| REACH (MM)                     | 370        | 376       | 380       | 392       | 408        | 417         |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        | 72,5°       |
| HEAD TUBE ANGLE                | 71°        | 71°       | 71,5°     | 71,5°     | 72°        | 72°         |
| REAR CENTER (MM)               | 415        | 415       | 415       | 415       | 415        | 415         |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        | 200         |
| WHEELBASE (MM)                 | 994        | 995       | 1000      | 1016      | 1034       | 1048        |
| STEM (MM)                      | 70         | 70        | 80        | 80        | 100        | 100         |
| HANDLEBAR (MM)                 | 410        | 410       | 410       | 430       | 430        | 430         |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      | 175         |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        | 400         |

# X-ROAD 6.5 GR

Matte Mustard / Black

ROAD & GRAVEL / GRAVEL



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 Road Racing bicycles  |
| EN norm  | EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|       |  |
|-------|--|
| FRAME | Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready |
|-------|--|

|                |   |
|----------------|---|
| FORK           | X-ROAD Carbon Fork                          |
| BOTTOM BRACKET | SHIMANO, Cartridge Bearing                  |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS |
| FRONT AXLE     | SB02, TA12x119, M12xP1.5x8.5L, Black        |
| REAR AXLE      | SB02, TA12x165, M12xP1.5x14L, Black         |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO GRX RX610, 12-speed              |
| REAR DERAILLEUR | SHIMANO GRX RD-RX822, Shadow Plus Design |
| CRANKSET        | SHIMANO GRX FC-RX610, 40T                |
| CASSETTE        | SHIMANO SLX CS-M7101, 12-speed, 10-45T   |
| CHAIN           | SHIMANO DEORE CN-M6100                   |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO GRX RX610, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO GRX RX610, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE        |
| RIM FRONT  | DT Swiss R500, Disc, 28H, Tubeless Ready                   |
| TYRE FRONT | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX |
| HUB REAR   | SHIMANO FH-MT410, 28H, CL, 12x142mm, THRU Type AXLE        |
| RIM REAR   | DT Swiss R500, Disc, 28H, Tubeless Ready                   |
| TYRE REAR  | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX |
| SPOKES     | SAPIM Race, Stainless Black                                |
| NIPPLES    | SAPIM, Brass   |

### COCKPIT

|            |  |
|------------|--|
| STEM       | ONE Race ICR, Alloy, 31,8mm, -7°                                     |
| HANDLEBAR  | ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6° |
| GRIPS LEFT | ONE Handlebar Tape   |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Selle Royal Gravel         |
| SEATPOST       | ONE Race, Alloy, 27.2mm    |
| SEATPOST CLAMP | ONE CC-080A, 31,8mm, Black |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 500mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 70         | 70        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 470        | 490       | 510       | 530       | 550        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 523        | 530       | 540       | 570       | 590        |
| STACK HEIGHT (MM)              | 549        | 558       | 569       | 606       | 616        |
| REACH (MM)                     | 368        | 367       | 371       | 384       | 401        |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 71,5°     | 72°       | 73°       | 73°        |
| REAR CENTER (MM)               | 414        | 414       | 414       | 414       | 414        |
| HEAD TUBE LENGTH (MM)          | 125        | 135       | 145       | 180       | 190        |
| WHEELBASE (MM)                 | 990        | 992       | 995       | 1010      | 1030       |
| STEM (MM)                      | 80         | 80        | 90        | 100       | 110        |
| HANDLEBAR (MM)                 | 410        | 410       | 410       | 430       | 430        |
| CRANKSET (MM)                  | 170        | 172.5     | 172.5     | 175       | 175        |

# XR 6.3 GR

Matte Green Grey / Black

ROAD & GRAVEL / GRAVEL



## SPECIFICATION

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | ISO 4210-2 Road Racing bicycles  |
| EN norm  | EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|       |  |
|-------|--|
| FRAME | Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready |
|-------|--|

|                |   |
|----------------|---|
| FORK           | X-ROAD Carbon Fork                          |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm           |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS |
| FRONT AXLE     | SB02, TA12x119, M12xP1.5x8.5L, Black        |
| REAR AXLE      | SB02, TA12x165, M12xP1.5x14L, Black         |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO GRX RX400, 10-speed              |
| REAR DERAILLEUR | SHIMANO GRX RD-RX400, Shadow Plus Design |
| CRANKSET        | SHIMANO GRX FC-RX600, 40T                |
| CASSETTE        | SHIMANO CS-HG500, 10-speed, 11-36T       |
| CHAIN           | KMC X10                                  |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO GRX RX400, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO GRX RX400, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE        |
| RIM FRONT  | STARS J22GT, Disc, 28H                                     |
| TYRE FRONT | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX |
| HUB REAR   | SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE        |
| RIM REAR   | STARS J22GT, Disc, 28H                                     |
| TYRE REAR  | Schwalbe G-One Allround, RaceGuard, TL-Easy, 40-622, ADDIX |
| SPOKES     | SAPIM Race, Stainless Black                                |
| NIPPLES    | SAPIM, Brass   |

### COCKPIT

|            |  |
|------------|--|
| STEM       | ONE Race ICR, Alloy, 31,8mm, -7°                                     |
| HANDLEBAR  | ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6° |
| GRIPS LEFT | ONE Handlebar Tape   |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Selle Royal Gravel         |
| SEATPOST       | ONE Race, Alloy, 27.2mm    |
| SEATPOST CLAMP | ONE CC-080A, 31,8mm, Black |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 500mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 70         | 70        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 470        | 490       | 510       | 530       | 550        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 523        | 530       | 540       | 570       | 590        |
| STACK HEIGHT (MM)              | 549        | 558       | 569       | 606       | 616        |
| REACH (MM)                     | 368        | 367       | 371       | 384       | 401        |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 71,5°     | 72°       | 73°       | 73°        |
| REAR CENTER (MM)               | 414        | 414       | 414       | 414       | 414        |
| HEAD TUBE LENGTH (MM)          | 125        | 135       | 145       | 180       | 190        |
| WHEELBASE (MM)                 | 990        | 992       | 995       | 1010      | 1030       |
| STEM (MM)                      | 70         | 70        | 80        | 80        | 100        |
| HANDLEBAR (MM)                 | 410        | 410       | 410       | 430       | 430        |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |

# iXR 6.5

Matte Green Grey

iGRAVEL | Light / iXR



## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | BOSCH SX Performance, Battery CompactTube 400Wh |
| MAX. TORQUE         | 55Nm / 300%                                     |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)      |
| EN norm  | EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### E- BIKE PARTS

|         |                             |
|---------|-----------------------------|
| MOTOR   | BOSCH Performance SX, 55Nm  |
| CHARGER | BOSCH 2A                    |
| BATTERY | BOSCH CompactTube, 400Wh    |
| DISPLAY | BOSCH Mini Remote, Drop Bar |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | SU-E50-01, Alloy double-butted, Gravel Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, SH dropout, Integrated Cable Routing, Bike packing and mudguards ready |
| SUSPENSION FORK | RockShox RUDY Base, Tapered, SoloAir, 12x100mm axle, 40mm travel   |
| HEADSET         | ACROS AZX-1306S, ICR, ZS56/28.6 - ZS56/40, BlockLock 150°, Stainless Bearings  |
| REAR AXLE       | SB02, TA12x165, M12xP1.0x14.5mm, Black   |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO GRX RX610, 12-speed              |
| REAR DERAILLEUR | SHIMANO GRX RD-RX822, Shadow Plus Design |
| CRANKSET        | ONE Race, Alloy                          |
| CHAINRING       | ONE Race, 38T                            |
| CASSETTE        | SHIMANO SLX CS-M7101, 12-speed, 10-45T   |
| CHAIN           | SHIMANO DEORE CN-M6100                   |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO GRX RX610, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT64, 160mm                  |
| BRAKE REAR  | SHIMANO GRX RX610, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT64, 160mm                  |

### WHEELS

|                |  |
|----------------|--|
| WHEELSET FRONT | DT Swiss HG 1800 SPLINE®, CL, 12x100mm, Tubeless Ready                 |
| WHEELSET REAR  | DT Swiss HG 1800 SPLINE®, CL, 12x142mm, SH12, Tubeless Ready           |
| TYRE FRONT     | Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX |
| TYRE REAR      | Schwalbe G-One Allround Performance, RaceGuard, TL-Easy, 45-622, ADDIX |

### COCKPIT

|            |  |
|------------|--|
| STEM       | ONE Race ICR, Alloy, 31,8mm, -7°                                     |
| HANDLEBAR  | ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6° |
| GRIPS LEFT | ONE Handlebar Tape   |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Gravel                                  |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |

## GEOMETRY

| FRAME SIZE                     | 470mm (XS) | 490mm (S) | 510mm (M) | 530mm (L) | 550mm (XL) |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 70         | 70        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 470        | 490       | 510       | 530       | 550        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 530        | 540       | 550       | 570       | 590        |
| STACK HEIGHT (MM)              | 553        | 564       | 574       | 595       | 616        |
| REACH (MM)                     | 377        | 378       | 380       | 394       | 402        |
| SEAT TUBE ANGLE                | 74,5°      | 74°       | 73,5°     | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 70°        | 70,5°     | 70,5°     | 71°       | 71,5°      |
| REAR CENTER (MM)               | 445        | 445       | 445       | 445       | 445        |
| HEAD TUBE LENGTH (MM)          | 110        | 120       | 130       | 150       | 170        |
| WHEELBASE (MM)                 | 1039       | 1040      | 1045      | 1045      | 1070       |
| STEM (MM)                      | 80         | 80        | 90        | 100       | 110        |
| HANDLEBAR (MM)                 | 410        | 410       | 410       | 430       | 430        |
| CRANKSET (MM)                  | 165        | 165       | 170       | 170       | 170        |



\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# XR 9.8 GF

Gloss Carbon / Grey

ROAD & GRAVEL / GRAN FONDO



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |  |
|----------------|--|
| FRAME          | SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready. |
| FORK           | XR Hi Modulus Carbon Fork  |
| BOTTOM BRACKET | SHIMANO BB-72-41B, PressFit, shell 41x86.5mm   |
| HEADSET        | ACROS AIX-52SS, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings   |
| FRONT AXLE     | SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black   |
| REAR AXLE      | SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO ULTEGRA R8170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO ULTEGRA R8170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO ULTEGRA RD-R8150, Shadow Design              |
| CRANKSET         | SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T           |
| CHAIN            | SHIMANO XT CN-M8100                                  |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO RT-CL800, 160mm                     |
| BRAKE REAR  | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO RT-CL800, 140mm                     |

### WHEELS

|                |  |
|----------------|--|
| WHEELSET FRONT | DT Swiss ERC 1400 DICUT®, Carbon, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss ERC 1400 DICUT®, Carbon, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race           |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race           |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Vento Argo R5, Alloy |
| SEATPOST       | ONE Aero Carbon            |
| SEATPOST CLAMP | Frame Integrated Clamp     |

## GEOMETRY

| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) | 610mm (XXL) |
|--------------------------------|------------|-----------|-----------|-----------|------------|-------------|
| BB DROP (MM)                   | 77         | 77        | 77        | 77        | 77         | 77          |
| SEAT TUBE LENGTH (MM)          | 440        | 462       | 482       | 502       | 522        | 552         |
| EFFECTIVE TOP TUBE LENGTH (MM) | 525        | 532       | 545       | 569       | 591        | 610         |
| STACK HEIGHT (MM)              | 517        | 537       | 557       | 578       | 597        | 605         |
| REACH (MM)                     | 370        | 376       | 380       | 392       | 408        | 417         |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        | 72,5°       |
| HEAD TUBE ANGLE                | 71°        | 71°       | 71,5°     | 71,5°     | 72°        | 72°         |
| REAR CENTER (MM)               | 415        | 415       | 415       | 415       | 415        | 415         |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        | 200         |
| WHEELBASE (MM)                 | 994        | 995       | 1000      | 1016      | 1034       | 1048        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/110    | 420/110     |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      | 175         |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        | 400         |



\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# XR 9.7 GF

Gloss Carbon Red

ROAD & GRAVEL / GRAN FONDO



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|       |  |
|-------|--|
| FRAME | SU-51-01, Carbon XR Race High Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready. |
|-------|--|

|                |  |
|----------------|--|
| FORK           | XR Hi Modulus Carbon Fork  |
| BOTTOM BRACKET | SHIMANO BB-72-41B, PressFit, shell 41x86.5mm                     |
| HEADSET        | ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings |
| FRONT AXLE     | SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black                   |
| REAR AXLE      | SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black                |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO ULTEGRA R8170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO ULTEGRA R8170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO ULTEGRA RD-R8150, Shadow Design              |
| CRANKSET         | SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T           |
| CHAIN            | SHIMANO XT CN-M8100                                  |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO RT-CL800, 160mm                     |
| BRAKE REAR  | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO RT-CL800, 140mm                     |

### WHEELS

|                |  |
|----------------|--|
| WHEELSET FRONT | DT Swiss ER 1600 SPLINE®, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss ER 1600 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race   |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race   |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Vento Argo R5, Alloy |
| SEATPOST       | ONE Aero Carbon            |
| SEATPOST CLAMP | Frame Integrated Clamp     |

## GEOMETRY

|                                |            |           |           |           |            |             |
|--------------------------------|------------|-----------|-----------|-----------|------------|-------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) | 610mm (XXL) |
| BB DROP (MM)                   | 77         | 77        | 77        | 77        | 77         | 77          |
| SEAT TUBE LENGTH (MM)          | 440        | 462       | 482       | 502       | 522        | 552         |
| EFFECTIVE TOP TUBE LENGTH (MM) | 525        | 532       | 545       | 569       | 591        | 610         |
| STACK HEIGHT (MM)              | 517        | 537       | 557       | 578       | 597        | 605         |
| REACH (MM)                     | 370        | 376       | 380       | 392       | 408        | 417         |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        | 72,5°       |
| HEAD TUBE ANGLE                | 71°        | 71°       | 71,5°     | 71,5°     | 72°        | 72°         |
| REAR CENTER (MM)               | 415        | 415       | 415       | 415       | 415        | 415         |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        | 200         |
| WHEELBASE (MM)                 | 994        | 995       | 1000      | 1016      | 1034       | 1048        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/110    | 420/110     |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      | 175         |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        | 400         |

# XR 9.5 GF

Gloss Grey / Red

ROAD & GRAVEL / GRAN FONDO



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|       |   |
|-------|---|
| FRAME | SU-52-01, Carbon XR Race Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BB86.5, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible, mudguards ready. |
|-------|---|

|                |   |
|----------------|---|
| FORK           | XR Mid Modulus Carbon Fork                        |
| BOTTOM BRACKET | SHIMANO BB-RS500PB, PressFit, shell 41x86.5mm     |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS       |
| FRONT AXLE     | SB02-LT, TA12x119, M12xP1.5x8.5L, Light, Black    |
| REAR AXLE      | SB02-LT, TA12x171.5, M12xP1.0x14.5L, Light, Black |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO 105 R7170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO 105 R7170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO 105 RD-R7150, Shadow Design              |
| CRANKSET         | SHIMANO 105 FC-R7100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO 105 CS-R7100, 12 speed, 11-34T           |
| CHAIN            | SHIMANO DEORE CN-M6100                           |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss E 1800 SPLINE®, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss E 1800 SPLINE®, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race  |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 30-622, ADDIX Race  |

### COCKPIT

|           |  |
|-----------|--|
| STEM      | ONE Race ICR, Alloy, 31,8mm, -7°                                     |
| HANDLEBAR | ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6° |

### GRIPS LEFT

|            |                    |
|------------|--------------------|
| GRIPS LEFT | ONE Handlebar Tape |
|------------|--------------------|

### PARTS

|                |                        |
|----------------|------------------------|
| SADDLE         | Selle Royal Gravel     |
| SEATPOST       | ONE Aero Carbon        |
| SEATPOST CLAMP | Frame Integrated Clamp |

## GEOMETRY

|                                |            |           |           |           |            |             |
|--------------------------------|------------|-----------|-----------|-----------|------------|-------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) | 610mm (XXL) |
| BB DROP (MM)                   | 77         | 77        | 77        | 77        | 77         | 77          |
| SEAT TUBE LENGTH (MM)          | 440        | 462       | 482       | 502       | 522        | 552         |
| EFFECTIVE TOP TUBE LENGTH (MM) | 525        | 532       | 545       | 569       | 591        | 610         |
| STACK HEIGHT (MM)              | 517        | 537       | 557       | 578       | 597        | 605         |
| REACH (MM)                     | 370        | 376       | 380       | 392       | 408        | 417         |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        | 72,5°       |
| HEAD TUBE ANGLE                | 71°        | 71°       | 71,5°     | 71,5°     | 72°        | 72°         |
| REAR CENTER (MM)               | 415        | 415       | 415       | 415       | 415        | 415         |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        | 200         |
| WHEELBASE (MM)                 | 994        | 995       | 1000      | 1016      | 1034       | 1048        |
| STEM (MM)                      | 70         | 80        | 100       | 100       | 110        | 110         |
| HANDLEBAR (MM)                 | 410        | 410       | 410       | 410       | 430        | 430         |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      | 175         |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        | 400         |

# XR 6.5 GF

Matte Black Stealth

ROAD & GRAVEL / GRAN FONDO



# RR 9.8

Matte Carbon / Black

ROAD & GRAVEL / ROAD



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |  |
|----------------|--|
| FRAME          | Alu X6 Ultralite X-Road Race , Road Advanced Geometry, Smooth Welding, Disc Brake Flat mount, BB BSA 68mm, Integrated Cable Routing, Full Carbon front fork; mudguards ready |
| FORK           | X-ROAD Carbon Fork   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm  |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS  |
| FRONT AXLE     | SB02, TA12x119, M12xP1.5x8.5L, Black   |
| REAR AXLE      | SB02, TA12x165, M12xP1.5x14L, Black  |

### DRIVETRAIN

|                  |   |
|------------------|---|
| SHIFTERS LEFT    | SHIMANO 105 R7120, 2-speed                                  |
| SHIFTERS RIGHT   | SHIMANO 105 R7120, 12-speed                                 |
| FRONT DERAILLEUR | SHIMANO 105 FD-R7100, Down Swing, Down Pull, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO 105 RD-R7100, Shadow Design                         |
| CRANKSET         | SHIMANO 105 FC-R7100, Hollowtech II, 50-34T                 |
| CASSETTE         | SHIMANO 105 CS-R7100, 12 speed, 11-34T                      |
| CHAIN            | SHIMANO DEORE CN-M6100                                      |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO 105 R7120, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO 105 R7120, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE |
| RIM FRONT  | DT Swiss R500, Disc, 28H, Tubeless Ready            |
| TYRE FRONT | Schwalbe One Performance, RaceGuard, 30-622, ADDIX  |
| HUB REAR   | SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE |
| RIM REAR   | DT Swiss R500, Disc, 28H, Tubeless Ready            |
| TYRE REAR  | Schwalbe One Performance, RaceGuard, 30-622, ADDIX  |
| SPOKES     | SAPIM Race, Stainless Black                         |
| NIPPLES    | SAPIM, Alloy  |

### COCKPIT

|            |  |
|------------|--|
| STEM       | ONE Race ICR, Alloy, 31,8mm, -7°                                     |
| HANDLEBAR  | ONE Alloy, X-Race Aero, 31.8mm, Reach 70mm, Drop 127mm, Backsweep 6° |
| GRIPS LEFT | ONE Handlebar Tape   |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Selle Royal Gravel         |
| SEATPOST       | ONE Race, Alloy, 27.2mm    |
| SEATPOST CLAMP | ONE CC-080A, 31,8mm, Black |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 500mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 70         | 70        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 470        | 490       | 510       | 530       | 550        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 523        | 530       | 540       | 570       | 590        |
| STACK HEIGHT (MM)              | 549        | 558       | 569       | 606       | 616        |
| REACH (MM)                     | 368        | 367       | 371       | 384       | 401        |
| SEAT TUBE ANGLE                | 74,3°      | 73,8°     | 73,5°     | 73°       | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 71,5°     | 72°       | 73°       | 73°        |
| REAR CENTER (MM)               | 414        | 414       | 414       | 414       | 414        |
| HEAD TUBE LENGTH (MM)          | 125        | 135       | 145       | 180       | 190        |
| WHEELBASE (MM)                 | 990        | 992       | 995       | 1010      | 1030       |
| STEM (MM)                      | 70         | 80        | 100       | 100       | 110        |
| HANDLEBAR (MM)                 | 410        | 410       | 410       | 410       | 430        |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |

## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | PD-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible. |
| FORK           | RR Mid Modulus Carbon Fork, Rake 50mm   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm   |
| HEADSET        | ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings  |
| FRONT AXLE     | ONE, TA12x120, M12xP1.0x15L, Black  |
| REAR AXLE      | ONE, TA12x161, M12xP1.0x9.2mm, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO ULTEGRA R8170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO ULTEGRA R8170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO ULTEGRA RD-R8150, Shadow Design              |
| CRANKSET         | SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T           |
| CHAIN            | SHIMANO XT CN-M8100                                  |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO RT-CL800, 160mm                     |
| BRAKE REAR  | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO RT-CL800, 140mm                     |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Vento Argo R5, Alloy |
| SEATPOST       | ONE Carbon, Offset 13mm    |
| SEATPOST CLAMP | Frame Integrated Clamp     |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 74         | 74        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 471        | 486       | 503       | 522       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 503        | 524       | 540       | 555       | 576        |
| STACK HEIGHT (MM)              | 505        | 527       | 546       | 565       | 584        |
| REACH (MM)                     | 368        | 378       | 384       | 388       | 397        |
| SEAT TUBE ANGLE                | 75°        | 74,5°     | 74°       | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 72,5°     | 73°       | 73°       | 73°        |
| REAR CENTER (MM)               | 410        | 410       | 410       | 410       | 410        |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/100    |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.



# RR 9.8

Matte Carbon / White

ROAD & GRAVEL / ROAD



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | PD-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible. |
| FORK           | RR Mid Modulus Carbon Fork, Rake 50mm   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm   |
| HEADSET        | ACROS AIX-525S, ICR, OD56, IS52/28.6 - 40IPS, Stainless Bearings  |
| FRONT AXLE     | ONE, TA12x120, M12xP1.0x15L, Black  |
| REAR AXLE      | ONE, TA12x161, M12xP1.0x9.2mm, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO ULTEGRA R8170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO ULTEGRA R8170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO ULTEGRA FD-R8150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO ULTEGRA RD-R8150, Shadow Design              |
| CRANKSET         | SHIMANO ULTEGRA FC-R8100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO ULTEGRA CS-R8101, 12-speed, 11-34T           |
| CHAIN            | SHIMANO XT CN-M8100                                  |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO RT-CL800, 160mm                     |
| BRAKE REAR  | SHIMANO ULTEGRA R8170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO RT-CL800, 140mm                     |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                            |
|----------------|----------------------------|
| SADDLE         | Fizik Vento Argo R5, Alloy |
| SEATPOST       | ONE Carbon, Offset 13mm    |
| SEATPOST CLAMP | Frame Integrated Clamp     |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 74         | 74        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 471        | 486       | 503       | 522       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 503        | 524       | 540       | 555       | 576        |
| STACK HEIGHT (MM)              | 505        | 527       | 546       | 565       | 584        |
| REACH (MM)                     | 368        | 378       | 384       | 388       | 397        |
| SEAT TUBE ANGLE                | 75°        | 74,5°     | 74°       | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 72,5°     | 73°       | 73°       | 73°        |
| REAR CENTER (MM)               | 410        | 410       | 410       | 410       | 410        |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/100    |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# RR 9.6

Matte Carbon / Black

ROAD & GRAVEL / ROAD



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | PD-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible. |
| FORK           | RR Mid Modulus Carbon Fork, Rake 50mm   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm   |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS   |
| FRONT AXLE     | ONE, TA12x120, M12xP1.0x15L, Black  |
| REAR AXLE      | ONE, TA12x161, M12xP1.0x9.2mm, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO 105 R7170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO 105 R7170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO 105 RD-R7150, Shadow Design              |
| CRANKSET         | SHIMANO 105 FC-R7100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO 105 CS-R7100, 12 speed, 11-34T           |
| CHAIN            | SHIMANO DEORE CN-M6100                           |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                         |
|----------------|-------------------------|
| SADDLE         | Selle Royal Flex        |
| SEATPOST       | ONE Carbon, Offset 13mm |
| SEATPOST CLAMP | Frame Integrated Clamp  |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 74         | 74        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 471        | 486       | 503       | 522       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 503        | 524       | 540       | 555       | 576        |
| STACK HEIGHT (MM)              | 505        | 527       | 546       | 565       | 584        |
| REACH (MM)                     | 368        | 378       | 384       | 388       | 397        |
| SEAT TUBE ANGLE                | 75°        | 74,5°     | 74°       | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 72,5°     | 73°       | 73°       | 73°        |
| REAR CENTER (MM)               | 410        | 410       | 410       | 410       | 410        |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/100    |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# RR 9.6

Matte Carbon / White

ROAD & GRAVEL / ROAD



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | PD-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible. |
| FORK           | RR Mid Modulus Carbon Fork, Rake 45mm   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm   |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS   |
| FRONT AXLE     | ONE, TA12x120, M12xP1.0x15L, Black  |
| REAR AXLE      | ONE, TA12x161, M12xP1.0x9.2mm, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO 105 R7170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO 105 R7170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO 105 RD-R7150, Shadow Design              |
| CRANKSET         | SHIMANO 105 FC-R7100, Hollowtech II, 52-36T      |
| CASSETTE         | SHIMANO 105 CS-R7100, 12 speed, 11-34T           |
| CHAIN            | SHIMANO DEORE CN-M6100                           |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|                |   |
|----------------|---|
| WHEELSET FRONT | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x100mm, Tubeless Ready       |
| WHEELSET REAR  | DT Swiss ERC 1600 SPLINE®, Carbon, CL, 12x142mm, SH11, Tubeless Ready |
| TYRE FRONT     | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |
| TYRE REAR      | Schwalbe Pro One Evo, V-Guard, TL-Easy, 28-622, ADDIX Race            |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                         |
|----------------|-------------------------|
| SADDLE         | Selle Royal Flex        |
| SEATPOST       | ONE Carbon, Offset 13mm |
| SEATPOST CLAMP | Frame Integrated Clamp  |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 74         | 74        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 471        | 486       | 503       | 522       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 503        | 524       | 540       | 555       | 576        |
| STACK HEIGHT (MM)              | 505        | 527       | 546       | 565       | 584        |
| REACH (MM)                     | 368        | 378       | 384       | 388       | 397        |
| SEAT TUBE ANGLE                | 75°        | 74,5°     | 74°       | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 72,5°     | 73°       | 73°       | 73°        |
| REAR CENTER (MM)               | 410        | 410       | 410       | 410       | 410        |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/100    |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        |

# RR 9.5

Matte Carbon / Black

ROAD & GRAVEL / ROAD



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | PD-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible. |
| FORK           | RR Mid Modulus Carbon Fork, Rake 50mm   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm   |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS   |
| FRONT AXLE     | ONE, TA12x120, M12xP1.0x15L, Black  |
| REAR AXLE      | ONE, TA12x161, M12xP1.0x9.2mm, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO 105 R7170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO 105 R7170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO 105 RD-R7150, Shadow Design              |
| CRANKSET         | SHIMANO 105 FC-R7100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO 105 CS-R7100, 12 speed, 11-34T           |
| CHAIN            | SHIMANO DEORE CN-M6100                           |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE |
| RIM FRONT  | DT Swiss R500, Disc, 28H, Tubeless Ready            |
| TYRE FRONT | Schwalbe One Performance, RaceGuard, 28-622, ADDIX  |
| HUB REAR   | SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE |
| RIM REAR   | DT Swiss R500, Disc, 28H, Tubeless Ready            |
| TYRE REAR  | Schwalbe One Performance, RaceGuard, 28-622, ADDIX  |
| SPOKES     | SAPIM Race, Stainless Black                         |
| NIPPLES    | SAPIM, Alloy  |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                         |
|----------------|-------------------------|
| SADDLE         | Selle Royal Flex        |
| SEATPOST       | ONE Carbon, Offset 13mm |
| SEATPOST CLAMP | Frame Integrated Clamp  |

## GEOMETRY

|                                |            |           |           |           |            |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
| BB DROP (MM)                   | 74         | 74        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 471        | 486       | 503       | 522       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 503        | 524       | 540       | 555       | 576        |
| STACK HEIGHT (MM)              | 505        | 527       | 546       | 565       | 584        |
| REACH (MM)                     | 368        | 378       | 384       | 388       | 397        |
| SEAT TUBE ANGLE                | 75°        | 74,5°     | 74°       | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 72,5°     | 73°       | 73°       | 73°        |
| REAR CENTER (MM)               | 410        | 410       | 410       | 410       | 410        |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/100    |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        |

# RR 9.5

Matte Carbon / White

ROAD & GRAVEL / ROAD



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Road Racing bicycles   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | PD-FB-08, Carbon RR Mid Modulus, Road Advanced Geometry, Disc Brake Flat Mount, BSA 68, SH dropout, Thru Axle 142x12 mm, Inner cable routing, Di2 compatible. |
| FORK           | RR Mid Modulus Carbon Fork, Rake 50mm   |
| BOTTOM BRACKET | SHIMANO BB-RS501, BSA, shell 68mm   |
| HEADSET        | ACROS AIX-525, ICR, OD56, IS52/28.6 - 40IPS   |
| FRONT AXLE     | ONE, TA12x120, M12xP1.0x15L, Black  |
| REAR AXLE      | ONE, TA12x161, M12xP1.0x9.2mm, Black  |

### DRIVETRAIN

|                  |  |
|------------------|--|
| SHIFTERS LEFT    | SHIMANO 105 R7170, Di2, 2-speed                  |
| SHIFTERS RIGHT   | SHIMANO 105 R7170, Di2, 12-speed                 |
| FRONT DERAILLEUR | SHIMANO 105 FD-R7150, Down Swing, Brazed-On Type |
| REAR DERAILLEUR  | SHIMANO 105 RD-R7150, Shadow Design              |
| CRANKSET         | SHIMANO 105 FC-R7100, Hollowtech II, 50-34T      |
| CASSETTE         | SHIMANO 105 CS-R7100, 12 speed, 11-34T           |
| CHAIN            | SHIMANO DEORE CN-M6100                           |

### BRAKING SYSTEM

|             |   |
|-------------|---|
| BRAKE FRONT | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT70, 160mm                  |
| BRAKE REAR  | SHIMANO 105 R7170, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT70, 140mm                  |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | SHIMANO HB-RS470, 28H, CL, 12x100mm, THRU Type AXLE |
| RIM FRONT  | DT Swiss R500, Disc, 28H, Tubeless Ready            |
| TYRE FRONT | Schwalbe One Performance, RaceGuard, 28-622, ADDIX  |
| HUB REAR   | SHIMANO FH-RS470, 28H, CL, 12x142mm, THRU Type AXLE |
| RIM REAR   | DT Swiss R500, Disc, 28H, Tubeless Ready            |
| TYRE REAR  | Schwalbe One Performance, RaceGuard, 28-622, ADDIX  |
| SPOKES     | SAPIM Race, Stainless Black                         |
| NIPPLES    | SAPIM, Alloy  |

### COCKPIT

|            |                                   |
|------------|-----------------------------------|
| HANDLEBAR  | ONE Carbon Integrated Cockpit ICR |
| GRIPS LEFT | ONE Handlebar Tape                |

### PARTS

|                |                         |
|----------------|-------------------------|
| SADDLE         | Selle Royal Flex        |
| SEATPOST       | ONE Carbon, Offset 13mm |
| SEATPOST CLAMP | Frame Integrated Clamp  |

## GEOMETRY

| FRAME SIZE                     | 490mm (XS) | 520mm (S) | 540mm (M) | 560mm (L) | 580mm (XL) |
|--------------------------------|------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 74         | 74        | 70        | 70        | 70         |
| SEAT TUBE LENGTH (MM)          | 471        | 486       | 503       | 522       | 533        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 503        | 524       | 540       | 555       | 576        |
| STACK HEIGHT (MM)              | 505        | 527       | 546       | 565       | 584        |
| REACH (MM)                     | 368        | 378       | 384       | 388       | 397        |
| SEAT TUBE ANGLE                | 75°        | 74,5°     | 74°       | 73,5°     | 73°        |
| HEAD TUBE ANGLE                | 71,5°      | 72,5°     | 73°       | 73°       | 73°        |
| REAR CENTER (MM)               | 410        | 410       | 410       | 410       | 410        |
| HEAD TUBE LENGTH (MM)          | 100        | 120       | 140       | 160       | 180        |
| HANDLEBAR (MM)                 | 380/70     | 380/90    | 400/100   | 400/100   | 420/100    |
| CRANKSET (MM)                  | 165        | 165       | 170       | 172.5     | 172.5      |
| SEATPOST (MM)                  | 400        | 400       | 400       | 400       | 400        |



\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# eWAY 6.7

Matte Black

eCITY / eWAY



# eWAY 6.5

Gloss Grey

eCITY / eWAY



## SPECIFICATION

### BASE INFO

|                     |  |
|---------------------|--|
| E-SYSTEM            | BOSCH Performance, Battery PowerTube 625Wh |
| DISTANCE            | 150km                                      |
| MAX. TORQUE         | 75Nm / 300%                                |
| SUPPORT UP TO SPEED | 25km/h                                     |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)  |
| EN norm  | EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes) |

### E- BIKE PARTS

|         |                              |
|---------|------------------------------|
| MOTOR   | BOSCH Performance Line, 75Nm |
| CHARGER | BOSCH 2A                     |
| BATTERY | BOSCH PowerTube, 625Wh       |
| DISPLAY | BOSCH Intuiva 100            |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | RST Volant, 1-1/8", QR Type, 50mm travel   |
| HEADSET         | ONE PT-1866A-078-2 1-1/8", ID52, Integrated  |

### DRIVETRAIN

|                |                               |
|----------------|-------------------------------|
| SHIFTERS RIGHT | Enviolo Trekking 380 stepless |
| CRANKSET       | ONE Sport, Alloy              |
| CHAINRING      | Gates CARBON DRIVE CDX, 50T   |
| CASSETTE       | Gates CARBON DRIVE CDX, 24T   |
| CHAIN          | Gates CARBON DRIVE CDX        |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT26, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT26, 160mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | ONE, KTMD7F, 36H, QR Type, 6-Bolts       |
| RIM FRONT  | STARS J19DC, Disc, 36H                   |
| TYRE FRONT | SCALATO MONDANO, 50-622, Reflective Tape |
| HUB REAR   | Enviolo Trekking, 36H, 6-Bolts           |
| RIM REAR   | STARS J19DC, Disc, 36H                   |
| TYRE REAR  | SCALATO MONDANO, 50-622, Reflective Tape |
| SPOKES     | SAPIM Leader, Stainless Black            |
| NIPPLES    | SAPIM, Brass                             |

### COCKPIT

|             |                                |
|-------------|--------------------------------|
| STEM        | ONE, Alloy, 31.8mm, Adjustable |
| HANDLEBAR   | ONE Alloy, 38mm rise, 31.8mm   |
| GRIPS LEFT  | HERRMANS Line DD36             |
| GRIPS RIGHT | HERRMANS Line DD36             |

### PARTS

|                |                                |
|----------------|--------------------------------|
| SADDLE         | Selle Royal Explora            |
| SEATPOST       | ONE, Alloy, Suspension, 30,9mm |
| SEATPOST CLAMP | ONE FR-E04_01, 34,9mm, Black   |
| PEDALS         | Marwi SP-828                   |

### CITY/ SUV SET

|             |                    |
|-------------|--------------------|
| FRONT LIGHT | Spanninga X&O, 50  |
| REAR LIGHT  | Spanninga Pling XE |
| FENDER      | Alloy              |
| CARRIER     | Atran Velo System  |

## GEOMETRY

| FRAME SIZE                     | 460mm (S) | 500mm (M) | 540mm (L) | 580mm (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 62        | 62        | 62        | 62         |
| SEAT TUBE LENGTH (MM)          | 460       | 500       | 540       | 580        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 600       | 620       | 640        |
| STACK HEIGHT (MM)              | 604       | 626       | 648       | 670        |
| REACH (MM)                     | 390       | 397       | 403       | 409        |
| SEAT TUBE ANGLE                | 72,5°     | 72°       | 71,5°     | 71°        |
| HEAD TUBE ANGLE                | 69°       | 69,8°     | 70,5°     | 71,2°      |
| REAR CENTER (MM)               | 485       | 485       | 485       | 485        |
| HEAD TUBE LENGTH (MM)          | 170       | 180       | 190       | 200        |
| WHEELBASE (MM)                 | 1127      | 1133      | 1139      | 1145       |
| STEM (MM)                      | 75        |           |           | 105        |
| HANDLEBAR (MM)                 | 620       | 620       | 620       | 620        |
| CRANKSET (MM)                  | 170       | 170       | 170       | 170        |

## SPECIFICATION

### BASE INFO

|                     |  |
|---------------------|--|
| E-SYSTEM            | BOSCH Performance, Battery PowerTube 625Wh |
| DISTANCE            | 150km                                      |
| MAX. TORQUE         | 75Nm / 300%                                |
| SUPPORT UP TO SPEED | 25km/h                                     |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)  |
| EN norm  | EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes) |

### E- BIKE PARTS

|         |                              |
|---------|------------------------------|
| MOTOR   | BOSCH Performance Line, 75Nm |
| CHARGER | BOSCH 2A                     |
| BATTERY | BOSCH PowerTube, 625Wh       |
| DISPLAY | BOSCH Intuiva 100            |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | RST Volant, 1-1/8", QR Type, 50mm travel   |
| HEADSET         | ONE PT-1866A-078-2 1-1/8", ID52, Integrated  |

### DRIVETRAIN

|                |  |
|----------------|--|
| SHIFTERS RIGHT | SHIMANO NEXUS SL-C7000-5, REVOSHIFT, 5-speed |
| CRANKSET       | ONE Sport, Alloy                             |
| CHAINRING      | Gates CARBON DRIVE CDX, 46T                  |
| CASSETTE       | Gates CARBON DRIVE CDX, 34T                  |
| CHAIN          | Gates CARBON DRIVE CDX                       |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT30, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT30, 160mm              |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | ONE, 36H, Disc, 3/8"x100x140mm, Nut Type      |
| RIM FRONT  | STARS J19DC, Disc, 36H                        |
| TYRE FRONT | SCALATO MONDANO, 50-622, Reflective Tape      |
| HUB REAR   | SHIMANO NEXUS SG-C7000-5D, 36H, CL, 135x187mm |
| RIM REAR   | STARS J19DC, Disc, 36H                        |
| TYRE REAR  | SCALATO MONDANO, 50-622, Reflective Tape      |
| SPOKES     | SAPIM Leader, Stainless Black                 |
| NIPPLES    | SAPIM, Brass                                  |

### COCKPIT

|             |                                |
|-------------|--------------------------------|
| STEM        | ONE, Alloy, 31.8mm, Adjustable |
| HANDLEBAR   | ONE Alloy, 38mm rise, 31.8mm   |
| GRIPS LEFT  | HERRMANS Line DD36             |
| GRIPS RIGHT | HERRMANS Line DD36             |

### PARTS

|                |                                |
|----------------|--------------------------------|
| SADDLE         | Selle Royal Explora            |
| SEATPOST       | ONE, Alloy, Suspension, 30,9mm |
| SEATPOST CLAMP | ONE FR-E04_01, 34,9mm, Black   |
| PEDALS         | Marwi SP-828                   |

### CITY/ SUV SET

|             |                    |
|-------------|--------------------|
| FRONT LIGHT | Spanninga X&O, 50  |
| REAR LIGHT  | Spanninga Pling XE |
| FENDER      | Alloy              |
| CARRIER     | Atran Velo System  |

## GEOMETRY

| FRAME SIZE                     | 460mm (S) | 500mm (M) | 540mm (L) | 580mm (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 62        | 62        | 62        | 62         |
| SEAT TUBE LENGTH (MM)          | 460       | 500       | 540       | 580        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 600       | 620       | 640        |
| STACK HEIGHT (MM)              | 604       | 626       | 648       | 670        |
| REACH (MM)                     | 390       | 397       | 403       | 409        |
| SEAT TUBE ANGLE                | 72,5°     | 72°       | 71,5°     | 71°        |
| HEAD TUBE ANGLE                | 69°       | 69,8°     | 70,5°     | 71,2°      |
| REAR CENTER (MM)               | 485       | 485       | 485       | 485        |
| HEAD TUBE LENGTH (MM)          | 170       | 180       | 190       | 200        |
| WHEELBASE (MM)                 | 1127      | 1133      | 1139      | 1145       |
| STEM (MM)                      | 75        |           |           | 105        |
| HANDLEBAR (MM)                 | 620       | 620       | 620       | 620        |
| CRANKSET (MM)                  | 170       | 170       | 170       | 170        |

# eWAY 6.3

Matte Black

eCITY / eWAY



# eWAY 6.2

Matte Sand

eCITY / eWAY



## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | Bosch Active Line Plus, Bosch PT 625WH, 36V, integrated |
| MAX. TORQUE         | 50Nm / 270%   |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)  |
| EN norm  | EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes) |

### E- BIKE PARTS

|         |   |
|---------|---|
| MOTOR   | Bosch Active Line Plus, 36V, 250W, 50NM |
| CHARGER | Bosch 2A                                |
| BATTERY | Bosch Powertube 625WH, 36V, integrated  |
| DISPLAY | Bosch Intuvia display 100               |

### FRAMESET

|                 |                                    |
|-----------------|------------------------------------|
| FRAME           | Easy entry, integrated, aluminium  |
| SUSPENSION FORK | Suspension with 25mm travel, alloy |
| HEADSET         | Zoom PT-1866A-078 1-1", integrated |

### DRIVETRAIN

|                |                       |
|----------------|-----------------------|
| SHIFTERS RIGHT | Shimano Nexus 7 Speed |
| CRANKSET       | Samox EC33-BH3-F9-BNI |
| CHAINRING      | 38T                   |
| CASSETTE       | 18T                   |
| CHAIN          | KMC chain             |

### BRAKING SYSTEM

|        |                      |
|--------|----------------------|
| BRAKES | Hydraulic Disc Brake |
|--------|----------------------|

### WHEELS

|           |  |
|-----------|--|
| HUB FRONT | KTTC6F, 36H, 3"x100x140mm                              |
| HUB REAR  | Shimano Nexus SG-C3001-7D, 36H, center lock, 135x187mm |
| RIMS      | 28" Alloy double wall                                  |
| TYRES     | Scalato Mondano 50mm with puncture protection          |
| SPOKES    | Stainless steel  |

### COCKPIT

|           |                       |
|-----------|-----------------------|
| STEM      | Alloy, adjustable     |
| HANDLEBAR | Alloy, 620mm          |
| BELL      | Widek Paperclip       |
| GRIPS     | Ergonomic, adjustable |

### PARTS

|          |                           |
|----------|---------------------------|
| SADDLE   | Selle Royal Explora       |
| SEATPOST | Suspension, Alloy, 30.9mm |
| PEDALS   | Marwi SP-823, non-slip    |

### CITY/ SUV SET

|             |                              |
|-------------|------------------------------|
| FRONT LIGHT | Spanninga X&O, 30            |
| REAR LIGHT  | Pling! XE                    |
| FENDER      | Chamber Fender, CC973, alloy |
| CARRIER     | Alloy, with AVS              |
| KICKSTAND   | Atran Velo Rex               |
| FRAME LOCK  | AXA Block XXL                |
| CHAINCOVER  | Hesling Fluent               |

## GEOMETRY

| FRAME SIZE                     | 460mm (S) | 500mm (M) | 540mm (L) | 580mm (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 62        | 62        | 62        | 62         |
| SEAT TUBE LENGTH (MM)          | 460       | 500       | 540       | 580        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 600       | 620       | 640        |
| STACK HEIGHT (MM)              | 604       | 626       | 648       | 670        |
| REACH (MM)                     | 390       | 397       | 403       | 409        |
| SEAT TUBE ANGLE                | 72,5°     | 72°       | 71,5°     | 71°        |
| HEAD TUBE ANGLE                | 69°       | 69,8°     | 70,5°     | 71,2°      |
| REAR CENTER (MM)               | 485       | 485       | 485       | 485        |
| HEAD TUBE LENGTH (MM)          | 170       | 180       | 190       | 200        |
| WHEELBASE (MM)                 | 1127      | 1133      | 1139      | 1145       |
| STEM (MM)                      | 75        |           |           | 105        |
| HANDLEBAR (MM)                 | 620       | 620       | 620       | 620        |
| CRANKSET (MM)                  | 170       | 170       | 170       | 170        |

## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | BOSCH ACTIVE LINE PLUS; Battery PowerTube 500Wh |
| DISTANCE            | 140km   |
| MAX. TORQUE         | 50Nm / 270%                                     |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)  |
| EN norm  | EN17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes) |

### E- BIKE PARTS

|         |                                    |
|---------|------------------------------------|
| MOTOR   | BOSCH Active Line Plus, BES3, 50Nm |
| CHARGER | BOSCH 2A                           |
| BATTERY | BOSCH PowerTube, 500Wh             |
| DISPLAY | BOSCH Purion 200                   |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | RST Volant, 1-1/8", QR Type, 50mm travel   |
| HEADSET         | ONE PT-1866A-078-2 1-1/8", ID52, Integrated  |

### DRIVETRAIN

|                |  |
|----------------|--|
| SHIFTERS RIGHT | SHIMANO NEXUS SL-C3000-7 RevoSift, 7-speed |
| CRANKSET       | ONE Sport, Alloy                           |
| CHAINRING      | ONE, 38T                                   |
| CASSETTE       | SHIMANO NEXUS, Sprocket, 18T               |
| CHAIN          | KMC Z1eHX                                  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT30, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT30, 160mm              |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | ONE, 36H, Disc, 3/8"x100x140mm, Nut Type      |
| RIM FRONT  | STARS J19DC, Disc, 36H                        |
| TYRE FRONT | SCALATO MONDANO, 50-622, Reflective Tape      |
| HUB REAR   | SHIMANO NEXUS SG-C3001-7D, 36H, CL, 135x187mm |
| RIM REAR   | STARS J19DC, Disc, 36H                        |
| TYRE REAR  | SCALATO MONDANO, 50-622, Reflective Tape      |
| SPOKES     | SAPIM Leader, Stainless Black                 |
| NIPPLES    | SAPIM, Brass                                  |

### COCKPIT

|             |                                |
|-------------|--------------------------------|
| STEM        | ONE, Alloy, 31.8mm, Adjustable |
| HANDLEBAR   | ONE Alloy, 38mm rise, 31.8mm   |
| GRIPS LEFT  | HERRMANS Line DD36             |
| GRIPS RIGHT | HERRMANS Line DD36             |

### PARTS

|                |                              |
|----------------|------------------------------|
| SADDLE         | Selle Royal Explora          |
| SEATPOST       | ONE Sport, Alloy, 30.9mm     |
| SEATPOST CLAMP | ONE FR-E04.01, 34.9mm, Black |
| PEDALS         | Marwi SP-823                 |

### CITY/ SUV SET

|             |                    |
|-------------|--------------------|
| FRONT LIGHT | Spanninga X&O, 30  |
| REAR LIGHT  | Spanninga Pling XE |
| FENDER      | Alloy              |
| CARRIER     | Atran Velo System  |

## GEOMETRY

| FRAME SIZE                     | 460mm (S) | 500mm (M) | 540mm (L) | 580mm (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 62        | 62        | 62        | 62         |
| SEAT TUBE LENGTH (MM)          | 460       | 500       | 540       | 580        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 600       | 620       | 640        |
| STACK HEIGHT (MM)              | 604       | 626       | 648       | 670        |
| REACH (MM)                     | 390       | 397       | 403       | 409        |
| SEAT TUBE ANGLE                | 72,5°     | 72°       | 71,5°     | 71°        |
| HEAD TUBE ANGLE                | 69°       | 69,8°     | 70,5°     | 71,2°      |
| REAR CENTER (MM)               | 485       | 485       | 485       | 485        |
| HEAD TUBE LENGTH (MM)          | 170       | 180       | 190       | 200        |
| WHEELBASE (MM)                 | 1127      | 1133      | 1139      | 1145       |
| STEM (MM)                      | 75        |           |           | 105        |
| HANDLEBAR (MM)                 | 620       | 620       | 620       | 620        |
| CRANKSET (MM)                  | 170       | 170       | 170       | 170        |

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# eWAY 6.0

Matte Black



eCITY / eWAY

# iBLOX 6.3

Matte Black



iTOUR | Light / iBLOX

## SPECIFICATION

### BASE INFO

|                     |  |
|---------------------|--|
| E-SYSTEM            | BOSCH ACTIVE LINE; Battery PowerTube 500Wh |
| DISTANCE            | 120km                                      |
| MAX. TORQUE         | 40Nm / 340%                                |
| SUPPORT UP TO SPEED | 25km/h                                     |

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)   |
| EN norm  | EN 17406 Condition 1 Bicycles and EPAC used on regular paved surfaces. Tires intended to maintain ground contact (City and Urban bikes) |

### E- BIKE PARTS

|         |                               |
|---------|-------------------------------|
| MOTOR   | BOSCH Active Line, BES3, 40Nm |
| CHARGER | BOSCH 2A                      |
| BATTERY | BOSCH PowerTube, 500Wh        |
| DISPLAY | BOSCH Led Remote              |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | RST Volant, 1-1/8", QR Type, 50mm travel   |
| HEADSET         | ONE PT-1866A-078-2 1-1/8", ID52, Integrated  |

### DRIVETRAIN

|                |   |
|----------------|---|
| SHIFTERS RIGHT | SHIMANO NEXUS SL-C3000-7 RevoShift, 7-speed   |
| CRANKSET       | ONE Sport, Alloy                              |
| CHAINRING      | ONE, 38T                                      |
| CASSETTE       | SHIMANO NEXUS SG-C3001-7D, 36H, CL, 135x187mm |
| CHAIN          | KMC Z1eHX                                     |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 160mm              |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | ONE, 36H, Disc, 3/8"x100x140mm, Nut Type      |
| RIM FRONT  | STARS J19DC, Disc, 36H                        |
| TYRE FRONT | SCALATO MONDANO, 50-622, Reflective Tape      |
| HUB REAR   | SHIMANO NEXUS SG-C3001-7D, 36H, CL, 135x187mm |
| RIM REAR   | STARS J19DC, Disc, 36H                        |
| TYRE REAR  | SCALATO MONDANO, 50-622, Reflective Tape      |
| SPOKES     | SAPIM Leader, Stainless Black                 |
| NIPPLES    | SAPIM, Brass                                  |

### COCKPIT

|             |                               |
|-------------|-------------------------------|
| STEM        | ONE Alloy, 31.8mm, Adjustable |
| HANDLEBAR   | ONE Alloy, 38mm rise, 31.8mm  |
| GRIPS LEFT  | HERRMANS Line DD36            |
| GRIPS RIGHT | HERRMANS Line DD36            |

### PARTS

|                |                              |
|----------------|------------------------------|
| SADDLE         | ONE Comfort                  |
| SEATPOST       | ONE Sport, Alloy, 30,9mm     |
| SEATPOST CLAMP | ONE FR-E04_01, 34,9mm, Black |
| PEDALS         | Marwi SP-823                 |

### CITY/ SUV SET

|             |                    |
|-------------|--------------------|
| FRONT LIGHT | Spanninga X&O, 30  |
| REAR LIGHT  | Spanninga Pling XE |
| FENDER      | Steel              |
| CARRIER     | Atran Velo System  |

## GEOMETRY

| FRAME SIZE                     | 460mm (S) | 500mm (M) | 540mm (L) | 580mm (XL) |
|--------------------------------|-----------|-----------|-----------|------------|
| BB DROP (MM)                   | 62        | 62        | 62        | 62         |
| SEAT TUBE LENGTH (MM)          | 460       | 500       | 540       | 580        |
| EFFECTIVE TOP TUBE LENGTH (MM) | 580       | 600       | 620       | 640        |
| STACK HEIGHT (MM)              | 604       | 626       | 648       | 670        |
| REACH (MM)                     | 390       | 397       | 403       | 409        |
| SEAT TUBE ANGLE                | 72,5°     | 72°       | 71,5°     | 71°        |
| HEAD TUBE ANGLE                | 69°       | 69,8°     | 70,5°     | 71,2°      |
| REAR CENTER (MM)               | 485       | 485       | 485       | 485        |
| HEAD TUBE LENGTH (MM)          | 170       | 180       | 190       | 200        |
| WHEELBASE (MM)                 | 1127      | 1133      | 1139      | 1145       |
| STEM (MM)                      | 75        |           |           | 105        |
| HANDLEBAR (MM)                 | 620       | 620       | 620       | 620        |
| CRANKSET (MM)                  | 170       | 170       | 170       | 170        |

## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | BOSCH SX Performance, Battery CompactTube 400Wh |
| MAX. TORQUE         | 55Nm / 300%                                     |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)      |
| EN norm  | EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### E- BIKE PARTS

|         |                            |
|---------|----------------------------|
| MOTOR   | BOSCH Performance SX, 55Nm |
| CHARGER | BOSCH 2A                   |
| BATTERY | BOSCH CompactTube, 400Wh   |
| DISPLAY | BOSCH Purion 200           |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | SU-E41-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | HODAKA Monoshock, 1.5", 15x110mm axle, 45mm travel  |
| HEADSET         | ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°  |
| REAR AXLE       | SB02, TA12x171.5, M12xP1.0x14.5mm, Black  |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed |
| REAR DERAILLEUR | SHIMANO CUES RD-U4000, Shadow Design              |
| CRANKSET        | ONE Race, Alloy                                   |
| CHAINRING       | ONE Race, 38T, with Chain Guard                   |
| CASSETTE        | SHIMANO CUES CS-LG300, 9-speed, 11-46T            |
| CHAIN           | SHIMANO CN-LG500                                  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 180mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 180mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | STARS J30D, Disc, 32H                                    |
| TYRE FRONT | Schwalbe G-One Allround Performance, 29x2.25             |
| HUB REAR   | SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | STARS J30D, Disc, 32H                                    |
| TYRE REAR  | Schwalbe G-One Allround Performance, 29x2.25             |
| SPOKES     | SAPIM Galvanized Black                                   |
| NIPPLES    | SAPIM, Brass   |

### COCKPIT

|             |   |
|-------------|---|
| STEM        | ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder |
| HANDLEBAR   | ONE Alloy, 30mm rise, 31.8mm                          |
| GRIPS LEFT  | ONE Sport Ergo, Lock-On                               |
| GRIPS RIGHT | ONE Sport Ergo, Lock-On                               |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |
| PEDALS         | VP Components VP-836                                |

### CITY/ SUV SET

|             |                               |
|-------------|-------------------------------|
| FRONT LIGHT | HERRMANS H-Black MR4 E, 120lm |
| REAR LIGHT  | spanninga Pling XDS           |
| FENDER      | Alloy                         |
| CARRIER     | Atran Velo System             |

## GEOMETRY

| FRAME SIZE                     | 14" (XS) | 16" (S) | 18" (M) | 20" (L) | 22" (XL) |
|--------------------------------|----------|---------|---------|---------|----------|
| BB DROP (MM)                   | 60       | 60      | 60      | 60      | 60       |
| SEAT TUBE LENGTH (MM)          | 365      | 406     | 457     | 508     | 559      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 550      | 570     | 590     | 610     | 630      |
| STACK HEIGHT (MM)              | 632      | 642     | 651     | 660     | 670      |
| REACH (MM)                     | 369      | 386     | 403     | 421     | 438      |
| SEAT TUBE ANGLE                | 74°      | 74°     | 74°     | 74°     | 74°      |
| HEAD TUBE ANGLE                | 69°      | 69°     | 69°     | 69°     | 69°      |
| REAR CENTER (MM)               | 450      | 450     | 450     | 450     | 450      |
| HEAD TUBE LENGTH (MM)          | 110      | 120     | 130     | 140     | 150      |
| WHEELBASE (MM)                 | 1081     | 1102    | 1123    | 1144    | 1165     |
| STEM (MM)                      | 65       | 65      | 65      | 90      | 90       |
| HANDLEBAR (MM)                 | 700      | 700     | 700     | 700     | 700      |
| CRANKSET (MM)                  | 160      | 160     | 165     | 170     | 170      |
| SEATPOST (MM)                  | 350      | 350     | 350     | 350     | 350      |

# iBLOX 6.3 Low Step

Matte Black

iTOUR | Light / iBLOX



## SPECIFICATION

### BASE INFO

|                     |   |
|---------------------|---|
| E-SYSTEM            | BOSCH SX Performance, Battery CompactTube 400Wh |
| MAX. TORQUE         | 55Nm / 300%                                     |
| SUPPORT UP TO SPEED | 25km/h  |

### ISO AND EN NORM

|          |  |
|----------|--|
| ISO norm | EN 15194 Standard for 'Electronically Power Assisted Cycles' (EPAC)      |
| EN norm  | EN 17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### E- BIKE PARTS

|         |                            |
|---------|----------------------------|
| MOTOR   | BOSCH Performance SX, 55Nm |
| CHARGER | BOSCH 2A                   |
| BATTERY | BOSCH CompactTube, 400Wh   |
| DISPLAY | BOSCH Purion 200           |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | SU-E41-01, Alu 6061 T6, Touring Geometry, Smooth Welding, Bosch system ready, integrated battery, Inner Cable Routing |
| SUSPENSION FORK | HODAKA Monoshock, 1.5", 15x110mm axle, 45mm travel  |
| HEADSET         | ACROS AZF-604, ZS56/28.6 - ZS56/40, BlockLock 120°  |
| REAR AXLE       | SB02, TA12x171.5, M12xP1.0x14.5mm, Black  |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO CUES SL-U4000-9R, RAPIDFIRE Plus, 9-speed |
| REAR DERAILLEUR | SHIMANO CUES RD-U4000, Shadow Design              |
| CRANKSET        | ONE Race, Alloy                                   |
| CHAINRING       | ONE Race, 38T, with Chain Guard                   |
| CASSETTE        | SHIMANO CUES CS-LG300, 9-speed, 11-46T            |
| CHAIN           | SHIMANO CN-LG500                                  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 180mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 180mm              |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | SHIMANO HB-TC500-15-B, 32H, CL, 15x110mm, THRU Type AXLE |
| RIM FRONT  | STARS J30D, Disc, 32H                                    |
| TYRE FRONT | Schwalbe G-One Allround Performance, 29x2.25             |
| HUB REAR   | SHIMANO FH-TC500-HM-B, 32H, CL, 12X148mm, THRU Type AXLE |
| RIM REAR   | STARS J30D, Disc, 32H                                    |
| TYRE REAR  | Schwalbe G-One Allround Performance, 29x2.25             |
| SPOKES     | SAPIM Galvanized Black                                   |
| NIPPLES    | SAPIM, Brass   |

### COCKPIT

|             |   |
|-------------|---|
| STEM        | ONE ICR, Alloy, 31.8mm, Adjustable, with Light Holder |
| HANDLEBAR   | ONE Alloy, 30mm rise, 31.8mm                          |
| GRIPS LEFT  | ONE Sport Ergo, Lock-On                               |
| GRIPS RIGHT | ONE Sport Ergo, Lock-On                               |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Vivo                                    |
| SEATPOST       | ONE Sport, Alloy, 30,9mm                            |
| SEATPOST CLAMP | ONE CC-617, 34,9mm, with Quick Release level, Black |
| PEDALS         | VP Components VP-836                                |

### CITY/ SUV SET

|             |                               |
|-------------|-------------------------------|
| FRONT LIGHT | HERRMANS H-Black MR4 E, 120lm |
| REAR LIGHT  | spanninga Pling XDS           |
| FENDER      | Alloy                         |
| CARRIER     | Atran Velo System             |

## GEOMETRY

| FRAME SIZE                     | 15" (S) | 16" (M) | 18" (L) |
|--------------------------------|---------|---------|---------|
| BB DROP (MM)                   | 60      | 60      | 60      |
| SEAT TUBE LENGTH (MM)          | 365     | 432     | 485     |
| EFFECTIVE TOP TUBE LENGTH (MM) | 570     | 590     | 610     |
| STACK HEIGHT (MM)              | 642     | 651     | 660     |
| REACH (MM)                     | 386     | 403     | 421     |
| SEAT TUBE ANGLE                | 74°     | 74°     | 74°     |
| HEAD TUBE ANGLE                | 69°     | 69°     | 69°     |
| REAR CENTER (MM)               | 450     | 450     | 450     |
| HEAD TUBE LENGTH (MM)          | 120     | 130     | 140     |
| WHEELBASE (MM)                 | 1102    | 1123    | 1144    |
| STEM (MM)                      | 65      | 65      | 65      |
| HANDLEBAR (MM)                 | 700     | 700     | 700     |
| CRANKSET (MM)                  | 160     | 165     | 170     |
| SEATPOST (MM)                  | 350     | 350     | 350     |



\*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city/country.

superior.

# TEAM 24

Gloss Grey / Red

JUNIOR / TEAM



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Young Adult/t  |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6 Double Butted, Advanced Race Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount, |
| SUSPENSION FORK | RST Aerial Air, 1-1/8", 60mm travel  |
| BOTTOM BRACKET  | Thun Topaz, BSA  |
| HEADSET         | ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30  |

### DRIVETRAIN

|                 |                                   |
|-----------------|-----------------------------------|
| SHIFTERS RIGHT  | SRAM X5, Trigger Shifter, 9-speed |
| REAR DERAILLEUR | SRAM X7                           |
| CRANKSET        | ONE Sport, Alloy, 140mm, 28T      |
| CASSETTE        | SHIMANO CS-HG201, 9-speed, 11-36T |
| CHAIN           | KMC X9                            |

### BRAKING SYSTEM

|             |                                       |
|-------------|---------------------------------------|
| BRAKE FRONT | Alhonga HJ-372F, hydraulic disc brake |
| ROTOR FRONT | ALHONGA, 160mm                        |
| BRAKE REAR  | Alhonga HJ-372F, hydraulic disc brake |
| ROTOR REAR  | ALHONGA, 140mm                        |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | ONE Sport, 20H, Disc, M9x100mm, QR Type          |
| RIM FRONT  | STARS J18SF, Disc, 20H                           |
| TYRE FRONT | Schwalbe Rocket Ron Performance, 24x2.10", ADDIX |
| HUB REAR   | ONE Sport, 20H, CL, M10x135, QR Type             |
| RIM REAR   | STARS J18SF, Disc, 20H                           |
| TYRE REAR  | Schwalbe Rocket Ron Performance, 24x2.10", ADDIX |
| SPOKES     | SAPIM Laser, Stainless Black                     |
| NIPPLES    | SAPIM, Brass                                     |

### COCKPIT

|             |                              |
|-------------|------------------------------|
| HANDLEBAR   | ONE Alloy Integrated Cockpit |
| GRIPS LEFT  | ONE Junior Grip              |
| GRIPS RIGHT | ONE Junior Grip              |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Mini Vivo                               |
| SEATPOST       | ONE, Alloy, 27.2mm                                  |
| SEATPOST CLAMP | ONE CC-617, 31,8mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-400  |

## GEOMETRY

|                                |        |
|--------------------------------|--------|
| FRAME SIZE                     | 11"    |
| BB DROP (MM)                   | 25     |
| SEAT TUBE LENGTH (MM)          | 280    |
| EFFECTIVE TOP TUBE LENGTH (MM) | 500    |
| STACK HEIGHT (MM)              | 500    |
| REACH (MM)                     | 347    |
| SEAT TUBE ANGLE                | 73°    |
| HEAD TUBE ANGLE                | 68°    |
| REAR CENTER (MM)               | 390    |
| HEAD TUBE LENGTH (MM)          | 90     |
| WHEELBASE (MM)                 | 971    |
| HANDLEBAR (MM)                 | 580/45 |
| CRANKSET (MM)                  | 140    |

# RACER 27

Gloss Red

JUNIOR / RACER



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Young Adult/t  |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                 |   |
|-----------------|---|
| FRAME           | Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, SR dropout, SR Suntour XCT30, 1-1/8", Coil, QR Type, 100mm travel |
| SUSPENSION FORK | SR Suntour XCT30, 1-1/8", Coil, QR Type, 100mm travel   |
| BOTTOM BRACKET  | Thun Ibex, BSA  |
| HEADSET         | ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30   |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed |
| REAR DERAILLEUR | SHIMANO ACERA RD-M3020                            |
| CRANKSET        | ONE Sport, Alloy, 160mm, 32T                      |
| CASSETTE        | SHIMANO CS-HG31, 8-speed, 11-34T                  |
| CHAIN           | KMC Z8  |

### BRAKING SYSTEM

|             |                                     |
|-------------|-------------------------------------|
| BRAKE FRONT | SHIMANO MT200, hydraulic disc brake |
| ROTOR FRONT | SHIMANO SM-RT10, 160mm              |
| BRAKE REAR  | SHIMANO MT200, hydraulic disc brake |
| ROTOR REAR  | SHIMANO SM-RT10, 160mm              |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | SHIMANO HB-TX505, 32H, CL, M9x100mm, QR Type    |
| RIM FRONT  | STARS J20S, Disc, 32H                           |
| TYRE FRONT | Schwalbe Smart Sam, KevlarGuard, 27.5x2.10      |
| HUB REAR   | SHIMANO FH-TX505-8, 32H, CL, M10x135mm, QR Type |
| RIM REAR   | STARS J20S, Disc, 32H                           |
| TYRE REAR  | Schwalbe Smart Sam, KevlarGuard, 27.5x2.10      |
| SPOKES     | SAPIM Galvanized Black                          |
| NIPPLES    | SAPIM, Brass                                    |

### COCKPIT

|             |                              |
|-------------|------------------------------|
| STEM        | ONE, Alloy, 25.4mm, 15°      |
| HANDLEBAR   | ONE Alloy, 34mm rise, 25.4mm |
| GRIPS LEFT  | ONE Sport, Lock-On           |
| GRIPS RIGHT | ONE Sport, Lock-On           |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Mini Vivo                               |
| SEATPOST       | ONE Sport, Alloy, 27.2mm                            |
| SEATPOST CLAMP | ONE CC-617, 31,8mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-610  |

## GEOMETRY

|                                |          |           |
|--------------------------------|----------|-----------|
| FRAME SIZE                     | 13" (XS) | 15.5" (S) |
| BB DROP (MM)                   | 40       | 40        |
| SEAT TUBE LENGTH (MM)          | 343      | 393       |
| EFFECTIVE TOP TUBE LENGTH (MM) | 547      | 586       |
| STACK HEIGHT (MM)              | 566      | 566       |
| REACH (MM)                     | 383      | 424       |
| SEAT TUBE ANGLE                | 74°      | 74°       |
| HEAD TUBE ANGLE                | 69°      | 69°       |
| REAR CENTER (MM)               | 435      | 435       |
| HEAD TUBE LENGTH (MM)          | 90       | 90        |
| WHEELBASE (MM)                 | 1064     | 1104      |
| STEM (MM)                      | 35       | 35        |
| HANDLEBAR (MM)                 | 600      | 600       |
| CRANKSET (MM)                  | 160      | 160       |



# RACER 24

Gloss Teal

JUNIOR / RACER



# RACER 24

Gloss Red

JUNIOR / RACER



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Young Adult\   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout, |
| SUSPENSION FORK | SR Suntour XCT JR24, 1-1/8",Soft Spring, QR Type, 50mm travel                        |
| BOTTOM BRACKET  | Thun Ibex, BSA   |
| HEADSET         | ONE CH290TBW, 1-1/8  |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed |
| REAR DERAILLEUR | SHIMANO TOURNEY TX RD-TX800             |
| CRANKSET        | ONE Sport, Alloy, 140mm, 28T            |
| CASSETTE        | SHIMANO CS-HG31, 8-speed, 11-34T        |
| CHAIN           | KMC Z8                                  |

### BRAKING SYSTEM

|             |                        |
|-------------|------------------------|
| BRAKE FRONT | Saccon Junior, V-Brake |
| BRAKE REAR  | Saccon Junior, V-Brake |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | ONE Sport, 24H, M9x100mm, QR Type            |
| RIM FRONT  | STARS J19SZ, 24H                             |
| TYRE FRONT | Schwalbe Billy Bonkers, KevlarGuard, 24x2.00 |
| HUB REAR   | ONE Sport, 24H, M10x135, QR Type             |
| RIM REAR   | STARS J19SZ, 24H                             |
| TYRE REAR  | Schwalbe Billy Bonkers, KevlarGuard, 24x2.00 |
| SPOKES     | SAPIM Zinc                                   |
| NIPPLES    | SAPIM, Brass                                 |

### COCKPIT

|             |                         |
|-------------|-------------------------|
| STEM        | ONE, Alloy, 25.4mm, 15° |
| HANDLEBAR   | ONE Alloy, 25.4mm       |
| GRIPS LEFT  | ONE Junior Grip         |
| GRIPS RIGHT | ONE Junior Grip         |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Junior                                  |
| SEATPOST       | ONE, Alloy, 27.2mm                                  |
| SEATPOST CLAMP | ONE CC-617, 31,8mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-400  |

## GEOMETRY

|                                |     |
|--------------------------------|-----|
| FRAME SIZE                     | 11" |
| BB DROP (MM)                   | 25  |
| SEAT TUBE LENGTH (MM)          | 280 |
| EFFECTIVE TOP TUBE LENGTH (MM) | 500 |
| STACK HEIGHT (MM)              | 469 |
| REACH (MM)                     | 357 |
| SEAT TUBE ANGLE                | 73° |
| HEAD TUBE ANGLE                | 68° |
| REAR CENTER (MM)               | 390 |
| HEAD TUBE LENGTH (MM)          | 100 |
| WHEELBASE (MM)                 | 974 |
| STEM (MM)                      | 35  |
| HANDLEBAR (MM)                 | 540 |
| CRANKSET (MM)                  | 140 |

## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Young Adult\   |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                 |  |
|-----------------|--|
| FRAME           | Alu 6061 T6 Double Butted, Advanced Junior Geometry,1xOptimized, BB BSA, SR dropout, |
| SUSPENSION FORK | SR Suntour XCT JR24, 1-1/8",Soft Spring, QR Type, 50mm travel                        |
| BOTTOM BRACKET  | Thun Ibex, BSA   |
| HEADSET         | ONE CH290TBW, 1-1/8  |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO SL-RV400-8R, REVOSHIFT, 8-speed |
| REAR DERAILLEUR | SHIMANO TOURNEY TX RD-TX800             |
| CRANKSET        | ONE Sport, Alloy, 140mm, 28T            |
| CASSETTE        | SHIMANO CS-HG31, 8-speed, 11-34T        |
| CHAIN           | KMC Z8                                  |

### BRAKING SYSTEM

|             |                        |
|-------------|------------------------|
| BRAKE FRONT | Saccon Junior, V-Brake |
| BRAKE REAR  | Saccon Junior, V-Brake |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | ONE Sport, 24H, M9x100mm, QR Type            |
| RIM FRONT  | STARS J19SZ, 24H                             |
| TYRE FRONT | Schwalbe Billy Bonkers, KevlarGuard, 24x2.00 |
| HUB REAR   | ONE Sport, 24H, M10x135, QR Type             |
| RIM REAR   | STARS J19SZ, 24H                             |
| TYRE REAR  | Schwalbe Billy Bonkers, KevlarGuard, 24x2.00 |
| SPOKES     | SAPIM Zinc                                   |
| NIPPLES    | SAPIM, Brass                                 |

### COCKPIT

|             |                         |
|-------------|-------------------------|
| STEM        | ONE, Alloy, 25.4mm, 15° |
| HANDLEBAR   | ONE Alloy, 25.4mm       |
| GRIPS LEFT  | ONE Junior Grip         |
| GRIPS RIGHT | ONE Junior Grip         |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Junior                                  |
| SEATPOST       | ONE, Alloy, 27.2mm                                  |
| SEATPOST CLAMP | ONE CC-617, 31,8mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-400  |

## GEOMETRY

|                                |     |
|--------------------------------|-----|
| FRAME SIZE                     | 11" |
| BB DROP (MM)                   | 25  |
| SEAT TUBE LENGTH (MM)          | 280 |
| EFFECTIVE TOP TUBE LENGTH (MM) | 500 |
| STACK HEIGHT (MM)              | 469 |
| REACH (MM)                     | 357 |
| SEAT TUBE ANGLE                | 73° |
| HEAD TUBE ANGLE                | 68° |
| REAR CENTER (MM)               | 390 |
| HEAD TUBE LENGTH (MM)          | 100 |
| WHEELBASE (MM)                 | 974 |
| STEM (MM)                      | 35  |
| HANDLEBAR (MM)                 | 540 |
| CRANKSET (MM)                  | 140 |

# F.L.Y. 27

Matte Silver

JUNIOR / F.L.Y.



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Young Adult/t  |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount, |
| FORK           | Alloy 6061 T6, Advanced Junior, Disc Brake Flat mount   |
| BOTTOM BRACKET | Thun Topaz, BSA   |
| HEADSET        | ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30   |

### DRIVETRAIN

|                 |  |
|-----------------|--|
| SHIFTERS RIGHT  | SHIMANO ALIVIO SL-M3100-R, RAPIDFIRE Plus, 9-speed |
| REAR DERAILLEUR | SHIMANO ALIVIO RD-M3100, Shadow Design             |
| CRANKSET        | ONE Sport, Alloy, 160mm, 32T                       |
| CASSETTE        | SHIMANO CS-HG201, 9-speed, 11-36T                  |
| CHAIN           | KMC X9   |

### BRAKING SYSTEM

|             |                                       |
|-------------|---------------------------------------|
| BRAKE FRONT | Alhonga HJ-372F, hydraulic disc brake |
| ROTOR FRONT | ALHONGA, 160mm                        |
| BRAKE REAR  | Alhonga HJ-372F, hydraulic disc brake |
| ROTOR REAR  | ALHONGA, 160mm                        |

### WHEELS

|            |   |
|------------|---|
| HUB FRONT  | ONE Sport, 28H, Disc, M9x100mm, QR Type           |
| RIM FRONT  | STARS J20S, Disc, 28H                             |
| TYRE FRONT | Schwalbe Smart Sam Performance, 27.5x2.10", ADDIX |
| HUB REAR   | ONE Sport, 28H, CL, M10x135, QR Type              |
| RIM REAR   | STARS J20S, Disc, 28H                             |
| TYRE REAR  | Schwalbe Smart Sam Performance, 27.5x2.10", ADDIX |
| SPOKES     | SAPIM Galvanized Black                            |
| NIPPLES    | SAPIM, Brass                                      |

### COCKPIT

|             |                              |
|-------------|------------------------------|
| HANDLEBAR   | ONE Alloy Integrated Cockpit |
| GRIPS LEFT  | ONE Junior Grip              |
| GRIPS RIGHT | ONE Junior Grip              |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Mini Vivo                               |
| SEATPOST       | ONE, Alloy, 27.2mm                                  |
| SEATPOST CLAMP | ONE CC-617, 31,8mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-400  |

## GEOMETRY

|                                |          |
|--------------------------------|----------|
| FRAME SIZE                     | 13" (XS) |
| BB DROP (MM)                   | 40       |
| SEAT TUBE LENGTH (MM)          | 330      |
| EFFECTIVE TOP TUBE LENGTH (MM) | 545      |
| STACK HEIGHT (MM)              | 499      |
| REACH (MM)                     | 402      |
| SEAT TUBE ANGLE                | 74°      |
| HEAD TUBE ANGLE                | 69°      |
| REAR CENTER (MM)               | 432      |
| HEAD TUBE LENGTH (MM)          | 90       |
| WHEELBASE (MM)                 | 1056     |
| HANDLEBAR (MM)                 | 660/45   |
| CRANKSET (MM)                  | 160      |
| SEATPOST (MM)                  | 350      |

# F.L.Y. 24 VB

Matte Silver

JUNIOR / F.L.Y.



## SPECIFICATION

### ISO AND EN NORM

|          |   |
|----------|---|
| ISO norm | ISO 4210-2 Young Adult/t  |
| EN norm  | EN17406 Condition 2 For on and Off-Road riding and drops less than 15cm |

### FRAMESET

|                |   |
|----------------|---|
| FRAME          | Alu 6061 T6 Double Butted, Advanced Junior Geometry, 1xOptimized, BB BSA, Inner cable routing, Disc Brake Flat mount, |
| FORK           | Alloy 6061 T6, Advanced Junior, V-Brake   |
| BOTTOM BRACKET | Thun Topaz, BSA   |
| HEADSET        | ONE CHS0926 FIT8, 1-1/8", IS41/28.6 - IS41/30   |

### DRIVETRAIN

|                 |   |
|-----------------|---|
| SHIFTERS RIGHT  | SHIMANO ALTUS SL-M315-8R, RAPIDFIRE Plus, 8-speed |
| REAR DERAILLEUR | SHIMANO ACERA RD-M3020                            |
| CRANKSET        | ONE Sport, Alloy, 140mm, 28T                      |
| CASSETTE        | SHIMANO CS-HG31, 8-speed, 11-34T                  |
| CHAIN           | KMC Z8  |

### BRAKING SYSTEM

|             |                        |
|-------------|------------------------|
| BRAKE FRONT | Saccon Junior, V-Brake |
| BRAKE REAR  | Saccon Junior, V-Brake |

### WHEELS

|            |  |
|------------|--|
| HUB FRONT  | ONE Sport, 24H, M9x100mm, QR Type                        |
| RIM FRONT  | STARS J19SZ, 24H   |
| TYRE FRONT | Schwalbe CX Comp, KevlarGuard, 24x1.75", Reflective tape |
| HUB REAR   | ONE Sport, 24H, M10x130, QR Type                         |
| RIM REAR   | STARS J19SZ, 24H   |
| TYRE REAR  | Schwalbe CX Comp, KevlarGuard, 24x1.75", Reflective tape |
| SPOKES     | SAPIM Galvanized Black                                   |
| NIPPLES    | SAPIM, Brass   |

### COCKPIT

|             |                              |
|-------------|------------------------------|
| HANDLEBAR   | ONE Alloy Integrated Cockpit |
| GRIPS LEFT  | ONE Junior Grip              |
| GRIPS RIGHT | ONE Junior Grip              |

### PARTS

|                |   |
|----------------|---|
| SADDLE         | Selle Royal Mini Vivo                               |
| SEATPOST       | ONE, Alloy, 27.2mm                                  |
| SEATPOST CLAMP | ONE CC-617, 31,8mm, with Quick Release level, Black |
| PEDALS         | Marwi SP-400  |

## GEOMETRY

|                                |        |
|--------------------------------|--------|
| FRAME SIZE                     | 11"    |
| BB DROP (MM)                   | 25     |
| SEAT TUBE LENGTH (MM)          | 280    |
| EFFECTIVE TOP TUBE LENGTH (MM) | 500    |
| STACK HEIGHT (MM)              | 448    |
| REACH (MM)                     | 363    |
| SEAT TUBE ANGLE                | 73°    |
| HEAD TUBE ANGLE                | 68°    |
| REAR CENTER (MM)               | 388    |
| HEAD TUBE LENGTH (MM)          | 100    |
| WHEELBASE (MM)                 | 966    |
| HANDLEBAR (MM)                 | 580/45 |
| CRANKSET (MM)                  | 140    |



[WWW.SUPERIORBIKES.COM](http://WWW.SUPERIORBIKES.COM)

